

# CERIO Corporation

## CenOS 5.0 User Manual For

### OW-400 A1

eXtreme Power Wave2 4X 11N/ac 2.4/5Ghz 2x2  
+18dBi Outdoor Bridge/AP



## Content

- 1. Device and Software Configuration ..... 6**
  - 1.1 Device & Antenna & RJ45 Ports appearance ..... 6
  - 1.2 Setup preparation of AP ..... 6
  - 1.3 Login Web Page ..... 9
- 2. Operating Mode Introduction ..... 10**
  - 2.1 Access Point Mode (Default) ..... 10
  - 2.2 Client Bridge + Repeater Mode ..... 12
  - 2.3 WISP + Repeater AP Mode ..... 13
  - 2.4 CAP mode (Centralizes Access Point) ..... 14
- 3. System Configuration ..... 15**
  - 3.1 Management ..... 15
  - 3.2 Configure Time Server ..... 17
  - 3.3 SNMP ..... 19
  - 3.4 Configure Time Policy ..... 20
- 4. Access Point mode ..... 22**
  - 4.1 VLAN Setup ..... 22
    - # Network Setup ..... 23
    - # Network Pull-down menu ..... 24
  - 4.1.1 DHCP Server ..... 25
  - 4.1.2 Bandwidth Control ..... 26
  - 4.1.3 Radio 0(2.4G)/1(5G) Access Point Setup ..... 27
  - 4.1.4 MAC Filter ..... 30
  - 4.1.5 802.11r Fast Roaming Setup ..... 31
  - 4.2 Authentication ..... 33
    - 4.2.1 Enable Authentication function ..... 33
    - 4.2.2 Set Authentication function ..... 35

# Guest .....	35
# Local User .....	36
# OAuth2.0 .....	36
Sample for Google OAuth2.0 setup .....	37
Sample for Facebook OAuth2.0 setup .....	41
# POP3/IMAP Server .....	44
# Customize Page .....	45
# Language .....	47
# Walled Garden .....	47
# Privilege Address .....	47
# Profile .....	48
<b>4.3 RADIUS Server .....</b>	<b>49</b>
<b>4.4 RADIUS Account Setup .....</b>	<b>49</b>
<b>4.5 Wireless Configuration .....</b>	<b>50</b>
4.5.1 Radio 0 Setup (2.4G) .....	50
4.5.2 Radio 1 Setup(5G) .....	52
4.5.3 Advanced Setup .....	54
4.5.4 WMM Setup .....	56
4.5.5 WDS Setup .....	58
4.5.6 WDS Status .....	59
<b>5. CAP Mode .....</b>	<b>61</b>
5.1 Change Setup mode .....	61
5.2 VLAN Setup .....	61
5.3 AP Control .....	63
5.3.1 Scan Device .....	64
5.3.2 Batch Setup .....	65
5.3.3 AP Setup .....	67


5.3.4	Group Setup .....	68
5.3.5	Map Setup .....	68
5.3.6	Authentication Profile.....	70
5.3.7	Status .....	70
<b>6.</b>	<b>Client Bridge Mode .....</b>	<b>71</b>
6.1	Change Setup mode .....	71
6.2	Configure LAN Setup .....	71
6.3	Configure DHCP Setup.....	74
6.4	Wireless General Setup.....	76
6.4.1	Radio 0(2.4G) Basic Setup .....	76
6.4.2	Radio 1 (5G) Basic Setup .....	78
6.4.3	Advanced Setup .....	80
6.4.4	WMM Setup .....	83
6.4.5	Station Setup .....	85
6.4.6	Repeater AP Setup .....	87
6.4.7	MAC Filter Setup .....	89
6.4.8	802.11r Fast Roaming Setup .....	90
<b>7.</b>	<b>WISP Mode.....</b>	<b>93</b>
7.1	Change Setup mode .....	93
7.2	Configure WAN Setup .....	93
7.3	Configure LAN Setup .....	97
7.4	Configure DHCP Setup.....	100
7.5	Wireless General Setup.....	102
7.5.1	Radio 0 (2.4G) Basic Setup .....	102
7.5.2	Radio 1 (5G) Basic Setup .....	104
7.5.3	Advanced Setup .....	107
7.5.4	WMM Setup .....	109

7.5.5	Station Setup .....	111
7.5.6	Repeater AP Setup .....	113
7.5.7	MAC Filter Setup .....	115
7.5.8	802.11r Fast Roaming Setup .....	116
7.6	Advanced Setup .....	119
7.6.1	DMZ .....	119
7.6.2	IP Filter.....	120
7.6.3	MAC Filter.....	122
7.6.4	Virtual Server.....	123
7.6.5	Access Control .....	124
<b>8.</b>	<b>Utilities.....</b>	<b>126</b>
8.1	Profile Setting.....	126
8.2	System Upgrade .....	127
8.3	Network Utility.....	129
8.4	Reboot .....	130
<b>9.</b>	<b>Status .....</b>	<b>130</b>
9.1	Overview .....	131
9.2	Wireless Client.....	133
9.3	Online Users .....	133
9.4	Authentication Log.....	134
9.5	System Log.....	135
<b>10.</b>	<b>[ Other technical documents].....</b>	<b>136</b>
10.1	Point to Point / Multi-Point for WDS settings.....	136
10.2	Apply CERIO web authentication login page sample.....	137
<b>Appendix A. WEB GUI Valid Characters .....</b>		<b>144</b>

## 1. Device and Software Configuration

### 1.1 Device & Antenna & RJ45 Ports appearance


#### 1. 1T1R/2T2R Antenna Connector



**Notice**

*When the device's wireless signal selects the Radio output and only uses 1T1R, the main signal output position is ANT1, and ANT2 will have no signal output, Please refer to the manual 4.5.1 "Radio0 (2.4G)" Setup " instructions.*

#### 2. RJ-45 Ports Description




### 1.2 Setup preparation of AP


Please PC link to Device used cat5/6 Ethernet cable.

**The following setup uses a Windows PC, user OS may vary**


Basic connection diagram:




**Step 1:** Please click on the computer icon in the bottom right window, and click “Open Network and Internet settings”




**Step 2:** After click left side "Ethernet" function, click on the right side “Change adapter options” again.



**Step 3:** In **“Change adapter options”** Page. Please find Ethernet (Local LAN) and Click the right button on the mouse and Click **“Properties”**



**Step 4:** In Properties page to setting IP address, please find **“Internet Protocol Version 4 (TCP/IPv4)”** and double click or click **“OK”** button.






## Step 5 :

Select **“Use the following IP address”**, and fix in IP Address : 192.168.2.#

*ex. The # is any number by 1 to 253*

Subnet mask : 255.255.255.0


And Click **“OK”** to complete the fixed computer IP setting



## 1.3 Login Web Page

### Launch Web Browser

Launch as web browser to access the web management interface of system by entering the default IP Address, <http://192.168.2.254>, in the URL field, and then press Enter.




### System Login

Sign in  
<http://192.168.2.254>  
 Your connection to this site is not private

Username

Password


Default login Usermane is **“root”** and Password is **“default”**



## 2. Operating Mode Introduction


### 2.1 Access Point Mode (Default)

Please click on System -> Mode Setup and choose Access Point Mode




- It can be deployed as a traditional fixed wireless Access Point
- It allow wireless clients or Stations ( STA ) to access
- Supports DHCP Service, allowing for automated assigning of IP addresses to clients connecting to the network
- WDS Setup includes AES (Advanced Encryption Standard) Authentication
- This enables the wireless interconnection of Access Point in a IEEE802.11 network and accepts wireless
- Support Captive Portal authentication.

## Access Point Mode




1. Wireless 2.4G support 802.11 b/g/n
2. Wireless 5G support 802.11 a/n/ac
3. Support Wi-Fi roaming

## Access Point with WDS function



1. This Access Point mode built-in point to point (WDS) function.
2. Point-to-Point bridge can select use 2.4G or 5G radio.
3. When enable WDS function and disable Access Point (Wi-Fi) will become a pure WDS device.


## Access Point mode with web Authentication




1. Web login page can customized
2. Support Local Account / Remote RADIUS Server authentication / OAuth 2.0
3. Different VLANs can be configured for different authentication types.

## 2.2 Client Bridge + Repeater Mode


Please click on System ->Mode Setup and choose Client Bridge Mode



- It can be used as a Client Bridge + Repeater AP to receive wireless signals over last mile applications, helping WISPs deliver wireless broadband Internet service to new residential and business customers
- In this mode, the AP is enabled with DHCP Server functions. The wired clients of the AP are in the same subnet from Main Base Station and it accepts wireless connections from client devices. You can disabled the repeater extending AP function, which will enable the “AP Client ” function




Note: If Client Bridge used 5GHz connection to AP station then Repeater AP only use 2.4GHz.




## 2.3 WISP + Repeater AP Mode

Please click on System ->Mode Setup and choose WISP Mode




- It can be used as an WISP (Wireless Internet Service Provide) to receive wireless signals over last mile application, helping WISPs deliver wireless broadband Internet service to residents and business customers
- In the WISP (CPE) mode, the CenOS 5.0 AP is a gateway enabled with NAT and DHCP Server functions. The wired clients connected to APs are in different subnet from those connected to Main Base Station, and, in WISP (CPE) mode, it does not accept wireless association from wireless clients.




## 2.4 CAP mode (Centralizes Access Point)

Please click on System -> Mode Setup and choose CAP Mode



- Control Management of CenOS5.0 APs
- AP Management support 802.1Q VLAN infrastructure
- Centralized setting Access Point function and firmware upgrade.
- APs Group management for concept.



## 3. System Configuration

**Notice**

System ▾

- Mode Setup
- VLAN Setup
- Management
- Time Server
- SNMP
- Time Policy

There are common functions in any mode have Management / Time Server / SNMP and Time Policy.

Please refer to the following detailed instructions.

### 3.1 Management

Administrators can specify geographical location of the system via instructions in this page and modify system login password and select use system login protocol by 80, 443, 23, 22 Port.

The management page adds LED control on/off and system auto reboot function.

- Management
- Time Server
- SNMP
- Time Policy

**System Language**

Language:

---

**System Information**

System Name:

Description:

Location:

---

**Root Password**

New Root Password:

Check Root Password:

---

**Port Isolate**

Port Isolate:  Enable  Disable

---

**LED Control**

LED OFF:  Enable  Disable

**Login Methods**

HTTP:  80

HTTPS:  443

Telnet:  23

SSH:  22

Host Key Footprint:

Access WAN:  Enable  Disable

---

**System Log Setup**

Remote Server:

Port:


---

**Auto Reboot**

Type:

- **System Language:** Administrator can select system language for English and Traditional Chinese
- **System Information:** Administrator can set the system name / Description and Location.
- **Root Password:** Administrator can change system login password.
- **LED Control :** When system working the moment, device LED will flashes. Administrator can select close the LED flashes in the function.
- **Ping Watchdog:** Ping Watchdog helps administrator to automatically reboot the system when ever there is a network or AP issue.

- **Ping Watchdog:** Enter IP address of remote device
- **Interval:** Ping interval of time.
- **Delay:** After system start, the set time value starts execution Ping watchdog.
- **Times of faults:** After the error exceeds the set value, system will auto reboot.
- **Login Methods:** Administrator can set system login protocol of the http/https/telnet and ssh.
- **Access WAN:** Administrator can enable and disable login access from WAN Public IP address(This function only for WISP Model)
- **System Log Setup:** Administrator can be backup system log or authentication log to remote server. Please enter IP address and port of remote syslog server.



- **Auto Reboot:** The functions can Auto-reboot the system by Date/time management.
  - **Daily :** Setting time to system reboot.

- **Weekly :** Setting frequency (ex. Weekly) and time of system reboot



**Auto Reboot**

Type: Week

Weekly:  Sun  Mon  Tue  Wed  
 Thu  Fri  Sat

Hour: 00

Minute: 00

- **Monthly** : Setting Every month, fixed date and time to system reboot

**Auto Reboot**

Type: Month


Monthly:  01  02  03  04  05  06  07  08  09  10  
 11  12  13  14  15  16  17  18  19  20  
 21  22  23  24  25  26  27  28  29  30  
 31

Hour: 00

Minute: 00

Click **“Save”** button to save your changes. And click **“Reboot”** button to activate your changes

## 3.2 Configure Time Server



Administrator can select manual or via a NTP server to modify system time for the right local time.

If select update the system time for manual, when administrator reboot system the system time will reply default.

If select update the system time for the NTP Server, system must set gateway and DNS server, the system can be connected internet.

**System Time**

**Local Time**

**Mode**  NTP Server  Manual

---

**User Setup**

**Date(Y/M/D)**

**Time(H:M:S)**    (GMT+8:00)

- **Mode:** Administrator can select NTP Server or Manual.
  - **NTP Server:** System can auto update the system time. Administrator needs setting as NTP Server.

**NTP Server**

**Default NTP Server**

**NTP Server**

**Time Zone**

**Daylight Saving Time**  Enable  Disable

- ✓ **Default NTP Server:** Administrator can select NTP Server.
- ✓ **NTP Server:** Administrator can setting as NTP Server.
- ✓ **Time Zone:** Administrator can select a desired time zone from the drop-down list.
- ✓ **Daylight saving Time:** Enable or disable Daylight saving.
- **Manual:** Administrator must to set the system time.


**User Setup**

**Date(Y/M/D)**

**Time(H:M:S)**    (GMT+8:00)

Click **“Save”** button to save your changes. And click **“Reboot”** button to activate your changes


## 3.3 SNMP



SNMP is an application-layer protocol that provides a message format for communication between SNMP managers and agents. By enabling SNMP function, the administrator can obtain the system information remotely.

Please click on **System -> SNMP** and follow the below setting.

### SNMP v2c function



SNMP v2c


Active  Enable   Disable

RO Community

RW Community

- **Active:** Administrator can select Enable or Disable the service.
- **RO Community:** Set a community string to authorize read-only access.
- **RW Community:** Set a community string to authorize read/write access.

### SNMP v3 function



SNMP v3

Active  Enable   Disable

RO Username

RO Password

RW Username

RW Password

- **Active:** Administrator can select Enable or Disable the service.
- **RO username:** Set a community string to authorize read-only access.
- **Ro password:** Set a password to authorize read-only access.
- **RW username:** Set a community string to authorize read/write access.
- **RW password:** Set a password to authorize read/write access.

## SNMP Trap

Events such as cold start interface up & down, and association & disassociation will report to an assigned server.

**SNMP Trap**

**Active**   
  **Enable**   
  **Disable**

**Community**

**IP 1**

**IP 2**


**IP 3**

**IP 4**

- **Active:** Administrator can select Enable or Disable the service.
- **Community:** Set a community string required by the remote host computer that will receive trap messages or notices send by the system.
- **IP(1~4) :** Enter the IP addresses of the remote hosts to receive trap messages.

Click **“Save”** button to save your changes. And click **“Reboot”** button to activate your changes

## 3.4 Configure Time Policy



#	Comment	Mode	Edit
1	Policy 1	On Schedule	<a href="#">Edit</a>
2	Policy 2	On Schedule	<a href="#">Edit</a>
3	Policy 3	On Schedule	<a href="#">Edit</a>
4	Policy 4	On Schedule	<a href="#">Edit</a>
5	Policy 5	On Schedule	<a href="#">Edit</a>
6	Policy 6	On Schedule	<a href="#">Edit</a>

Please click **Edit** button to setting Time Policy rules.

**Time Policy Rules**

**Comment**

**Mode**  **On Schedule**  **Out Of Schedule**

**Policy List** Create New Policy

#	Sun	Mon	Tue	Wed	Thu	Fri	Sat	Time	Action
-	-	-	-	-	-	-	-	-	-

- **Comment:** Enter the description of Time Policy rule.
- **Mode:** Administrator can select On schedule or Out of schedule to execution the rules.

### Create New Policy button:

Administrator can set time for week / start time and end time.

**Time Policy Rules**

**Day of Week**

Sun  Mon  Tue

Wed  Thu  Fri


Sat

**Start Time**

**End Time**

Click "Save" button to add schedule to policy. There are 10 schedule maximum allowed in the each time policy. All schedules can be edited or removed in the each time policy. Click **Reboot** button to activate your changes.

## 4. Access Point mode




When AP mode is chosen, the system can be configured as an Access Point. This section provides detailed explanation for users to configure in the AP mode with help of illustrations. In the AP mode, functions listed in the table below are also available from the Web-based GUI interface.

### 4.1 VLAN Setup

Here are the instructions to setup the local IP Address / Netmask / Gateway / DNS and management Access Point 2.4G or 5G Radio on/off. Administrators can change settings such as LAN Spanning Tree and Tag VLAN functions.

#	VLAN Mode	Flag	IP Address	Netmask	Radio 0	Radio 1	Action
0	On	Native ETH0 Access Control	192.168.2.254	255.255.255.0	2.4_0_0	5G_0_0	Network
1	Off	ETH0.101	-	-	2.4_1_0	5G_1_1	Network
2	Off	ETH0.102	-	-	2.4_2_0	5G_2_1	Network
3	Off	ETH0.103	-	-	2.4_3_0	5G_3_1	Network
4	Off	ETH0.104	-	-	2.4_4_0	5G_4_1	Network
5	Off	ETH0.105	-	-	2.4_5_0	5G_5_1	Network



- **VLAN Mode** : Display on/off for the VLAN network.
- **Flag** : Display master VLAN and VLAN Tag No. information.
- **IP Address** : Display IP Address for VLAN Network.
- **NetMask** : Display IP netmask.
- **Radio 0** : Display radio 2.4G SSID name.
- **Radio 1** : Display radio 5G SSID name.

- **Default Gateway:** Set IP address of Gateway.
- **Port Isolate :** When enable web authentication function, administrator can chooses Ethernet port whether used web authentication. (This function need enable System → Authentication function)



- **Enable:** If chooses enable this function then client connection Ethernet port will need web authentication too. When enable this function system will only 1 VLAN and 1 ESSID.



- **Disable:** If chooses disable this function then client connection Ethernet port will not be intercepted using web authentication. Wired client network basis on VLAN0. When disable this function system can use 16 VLAN and 16 ESSID.




- **DNS#:** Set IP address of DNS.
- **Action :** The button can set VLAN network functions and radio functions.

## # Network Setup

Network button

Administrator can click  button to set VLAN network functions.



- **VLAN Mode :** Administrator can select Enable or disable for the VLAN Network.




**Notice** At least one VLAN will always be enabled by default

- **IP Mode** : Administrator can select enable or disable function for VLAN IP.
- **IP Address/ NetMask** : Administrator can set IP address and netmask for the VLAN.

## Management

- **Access Point 0** : Administrator can Enable or Disable 2.4G Radio.
- **Access Point 1** : Administrator can Enable or Disable 5G Radio.
- **802.1d Spanning Tree** : The spanning tree network protocol provides a loop free topology for a bridged LAN between LAN interface and 8 WDS interfaces from wds0 to wds7. The Spanning Tree Protocol, which is also referred to as STP, is defined in the IEEE Standard 802.1d




- **Control Port** : Administrator can select one of the VLAN as managed AP.
- **IAPP** : Administrator can select radio 2.4G or 5G for IAPP roaming. *(the IAPP condition must use WPA2-PSK Wi-Fi security and AES algorithm)*
- **VLAN Tag Setup**: Set the VLAN used tags.

## # Network Pull-down menu


Administrator can set DHCP Server and 2.4/5G security for the access point and set 802.11r fast roaming.

Please click  pull-down button.






## 4.1.1 DHCP Server



Administrator can select enable / disable the function



DHCP Setup	
Start IP	<input type="text"/>
End IP	<input type="text"/>
Netmask	<input type="text" value="255.255.255.0"/>
Gateway	<input type="text"/>
DNS1 IP	<input type="text"/>
DNS2 IP	<input type="text"/>
WINS IP	<input type="text"/>
Domain	<input type="text"/>
Lease Time	<input type="text" value="86400"/>

- **Start IP:** Set Start IP address for DHCP Service.
- **End IP:** Set End IP address for DHCP Service.
- **Netmask:** Set IP Netmask, the default is 255.255.255.0
- **Gateway:** Set Gateway IP address for DHCP Service.
- **DNS(1-2) IP :** Set DNS IP address for DHCP Service.
- **WINS IP:** Enter IP address of the Windows Internet Name Service (WINS) server; this is optional.
- **Domain:** Enter the domain name for this network.
- **Lease Time:** The IP addresses given out by the DHCP server will only be valid for the duration specified by the lease time. Increasing the time ensure client operation without interruptions, but could introduce potential conflicts. Lowering the lease time will avoid potential address conflicts, but might cause more interruptions to the client while it will acquire new IP addresses from the DHCP server. Default is **86400** seconds

### DHCP Client List

Administrator can view IP address used status of client users on each DHCP Server.

DHCP Client List				
#	IP Address	MAC Address	Expired	Action
-	-	-	-	-

### Static Lease IP Setup

Administrator can set be delivered fixed IP address to the users.

**Static Lease IP Setup**

Comment


IP Address

MAC Address  Add

- **Comment:** Enter rule description.
- **IP Address:** Enter access point IP.
- **MAC Address:** Enter Client MAC Address of PC network.

Click “**Save**” button to save your changes. Then click **Reboot** button to activate your changes.

## 4.1.2 Bandwidth Control



Administrators can set bandwidth limit the max/min bandwidth of the Wi-Fi users, Bandwidth control can set IP/MASK , IP Range, Port(Service), SIP, RTP/RTSP and WEB.

**Bandwidth Control**

**Mode**     Enable                       Disable

**Airtime Fairness**     Enable                       Disable

- **Mode:** Administrator can Enable or Disable the function.
- **Airtime Fairness:** TX/RX traffic balancing, if device use point-to-point ( WDS or AP mode + Client Bridge) then recommended to enable it.

**Total Bandwidth Control**

**Mode**     Enable                       Disable

**Upload**     Kbps

**Download**     Kbps

- Administrator can set total bandwidth used limit in VLAN.


QoS RuleList							
#	Active	Rule Mode	Value1	Value2	Upload(Kbps)	Download(Kbps)	Comment
1	<input type="checkbox"/>	ANY			1024	1024	
2	<input type="checkbox"/>	ANY			1024	1024	
3	<input type="checkbox"/>	ANY			1024	1024	
4	<input type="checkbox"/>	ANY			1024	1024	
5	<input type="checkbox"/>	ANY			1024	1024	
6	<input type="checkbox"/>	ANY			1024	1024	
7	<input type="checkbox"/>	ANY			1024	1024	
8	<input type="checkbox"/>	ANY			1024	1024	
9	<input type="checkbox"/>	ANY			1024	1024	
10	<input type="checkbox"/>	ANY			1024	1024	

- **QoS Rule List:** Administrator can set bandwidth limit by IP/MASK, IP Range, Port(Service), SIP, RTP/RTSP, WEB protocol , each VLAN can set 10 bandwidth management rule.

Click **“Save”** button to save your changes. Then click **Reboot** button to activate your changes.


### 4.1.3 Radio 0(2.4G)/1(5G) Access Point Setup

Administrator can Enable or Disable radio 0/1 (2.4/5G) Wi-Fi. If radio 0/1 (2.4/5G) are enabled, administrators can set the SSID and security for the 2.4/5G access point.




Security		
<b>Access Point</b>	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
<b>ESSID</b>	<input type="text" value="Wi-Fi name"/>	
<b>SSID Visibility</b>	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
<b>Client Isolation</b>	<input type="radio"/> Enable	<input checked="" type="radio"/> Disable
<b>Connection Limit</b>	<input type="radio"/> Enable	<input checked="" type="radio"/> Disable
<b>User Limit</b>	<input type="text" value="64"/>	
<b>Security Type</b>	<input type="text" value="Open System"/>	

- **Access Point:** Administrator can Enable or Disable the radio 0/1 (2.4G/5G).
- **ESSID:** Administrator can set Wi-Fi SSID name
- **SSID Visibility:** Administrator can select Enable or Disable the Visibility.
- **Client Isolation:** Enable or Disable the client isolation function.
- **Connection Limit:** Administrator can select Enable or Disable WiFi connection Limit.
- **User Limit:** If select enable of the connection Limit function, administrator can set users connection limit.( Recommended 2.4G/5G limit 40/60 Wi-Fi Users)
- **Security Type:** Select the desired security type from the drop-down list; the options are Open System, WPA-PSK/WPA2-PSK and WPA/WPA2-Enterprise.



The screenshot shows a dropdown menu for 'Security Type'. The current selection is 'Open System'. The dropdown list includes the following options: 'Open System', 'WPA/WPA2 Personal', and 'WPA/WPA2 Enterprise'.

- **Open System:** Data is not unencrypted during transmission when this option is selected.
- **WPA-PSK/WPA2-PSK Personal:** WPA/WPA2 is short for W-Fi Protected Access-Pre-Shared Key. WPA/WPA2 uses the same encryption way with WPA, and the only difference between them is that WPA/WPA2 recreates a simple shared key, instead of using the user’s certification.



The screenshot shows the 'PassPhrase Settings' configuration page. It includes the following fields and options:

- WPA Mode:** Auto (WPA or WPA2)
- Cipher Type:** Auto
- Group Key Update Interval:** 600 Seconds
- PassPhrase:** (Empty text input field)
- WPS:** Radio buttons for 'Enable' and 'Disable' (currently 'Disable' is selected).
- WPS Push Button:** A green 'Push Button' button.


- ✓ **WPA Mode:** Administrator can select security for Auto or only WPA or only WPA2.
- ✓ **Cipher Type:** Administrator can select use AES or TKIP with WPA / WPA2 encryption method.

**AES** is short for “**Advanced Encryption Standard**”, The AES cipher is specified as a number of repetitions of transformation rounds that convert the input plaintext into the final output of ciphertext. Each round consists of several processing steps, including one that depends on the encryption key. A set of reverse rounds are applied to transform ciphertext back into the original plaintext using the same encryption key.

**TKIP** is short for “**Temporal Key Integrity Protocol**”, TKIP scrambles the keys using a hashing algorithm and, by adding an integrity-checking feature, ensures that the keys haven’t been tampered with.

- ✓ **Group Key Update Interval:** The time interval is for re-keying GTK (broadcast/multicast encryption keys) in seconds. Enter the time-length required; the default time is 600 seconds.
- ✓ **Pass Phrase:** Enter the ESSID pass phrase.
- ✓ **WPS:** Administrator can used WPS function to link WiFi client. If enabled, administrator can click the WPS Push Button.

- **WPA/WAP2-Enterprise**



The screenshot shows a configuration window titled "RADIUS Server Settings". It contains the following fields and options:

- Key Size:** Two radio button options, "64 Bits" (selected) and "128 Bits".
- Radius Server:** An empty text input field.
- Radius Port:** A text input field containing "1812" and a "Port" button to the right.
- Radius Secret:** An empty text input field.



- **Radius Server :** Enter the IP address of the Authentication RADIUS server.
- **Radius Port:** The port number used by Authentication RADIUS server. Use the default 1812 or enter port number specified.
- **Radius Secret:** The secret key for system to communicate with Authentication RADIUS server. Support 1 to 64 characters.

- **802.1x RADIUS Server Settings**

- **Key Size :** Enter the IP address of the Authentication RADIUS server.
- **Radius Server :** Enter the IP address of the Authentication RADIUS server.
- **Radius Port:** The port number used by Authentication RADIUS server. Use the default 1812 or enter port number specified.
- **Radius Secret:** The secret key for system to communicate with Authentication RADIUS server. Support 1 to 64 characters.


Click “**Save**” button to save your changes. Then click Reboot button to activate your changes..

## 4.1.4 MAC Filter



(1) **Only Deny List MAC** : Administrator can add wireless users MAC address in MAC list. The access point will deny connection in MAC address list.



(2) **Only Allow List MAC** : Administrator can add wireless users MAC address in MAC list. The access point will allow connection in MAC address list.



- **MAC Address:** Set managed MAC address of the client.
- **MAC Address List:** Display managed MAC address list.

Click **“Save”** button to save your changes. Then click Reboot button to activate your changes.

## 4.1.5 802.11r Fast Roaming Setup



The dual band Access Point supports 802.11r/802.11k function for 2.4G and 5G radio. 802.11r, which is the IEEE standard for fast roaming, introduces a new concept of roaming where the initial handshake with the new AP is done even before the client roams to the target AP.

**Notice** If this feature is enabled when using 802.11r fast roaming, the wireless user equipment must support 802.11k functionality to work properly

Fast Roaming Settings	
Mobility Domain	<input type="text" value="a1b2"/>
R0 Key Lifetime	<input type="text" value="10000"/>
Reassoc deadline	<input type="text" value="1000"/>
R0/NAS Identifier	<input type="text" value="ap.example.com"/>
R1 Identifier	<input type="text" value="000102030405"/>
R1 Push	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

- **Mobility Domain:** MDID is used to indicate a group of APs (within an ESS, i.e., sharing the same SSID) between which a STA can use Fast BSS Transition.

**Notice** This setting must be 2-octet of hex string codes. For example, enter 8c4d

- **R0 Key Lifetime:** Default lifetime of the PMK-RO in minutes, the default is 10000, administrator can setting 1~65535.
- **Reassoc deadline:** Reassociation deadline in time units (TUs / 1.024 ms; range 1000~65535). The default is 1000.

- **R0/NAS Identifier:** PMK-R0 Key Holder identifier. When using IEEE 802.11r, nas\_identifier must be set and must be between 1 and 48 octets long.
- **R1 Identifier:** PMK-R1 Key Holder identifier 6-octet identifier as a hex string.
- **R1 Push:** Administrator can select Enable or disable. If enable the function will automatically sent the R1 Key.

## R0 Key Holder:

To enable roaming between multiple AP devices, AP1 must key in the MAC Address of AP2, and AP2 must key in the MAC Address of AP1. The NAS Identifier and 128-bit Key should be identical in both AP settings. This will enable device roaming between the two Access Points.

**R0 Key holders**

**MAC Address**

**NAS Identifier**

**128-bit Key**  Add

- **MAC Address:** Administrators must enter the MAC Address of other AP
- **NAS Identifier:** Enter 1~48 octets of network domain name.
- **128-bit Key:** Enter Shared Key of 128 bit.

#	MAC位址	NAS Identifier	128-bit Key	執行
1	8c:4d:ea:00:11:22	cerio.com.tw	8c4dea00112233445566...	<span style="background-color: #f44336; color: white; padding: 2px 5px; border-radius: 3px;">刪除</span>

**R1 Key holders :** Enter a unified set of R1 Key Holder identification certification.

**R1 Key Holders**

**MAC Address**

**R1 Identifier**

**128-bit Key**  Add

- **MAC Address:** Enter the main roaming device MAC address
- **R1 Identifier:** Enter Shared identifier.
- **128-bit Key:** Enter Shared Key of 128 bit.


Click **“Save”** button to save your changes. Then click Reboot button to activate your changes.



## 4.2 Authentication

This function used to operate in **Access Point** mode, the function is for Web Authentication. It supports authentication for local users / RADIUS Server / OAuth2.0 and Guest. The system supports in N VLANs with web authentication.

Please click on System -> Authentication




When enable web authentication function, please does make the Access Point can be connected to gateway. Please refer to VLAN Setup. If the gateway IP address is set error address then web login page can't display

#	VLAN Mode	Authentication	Action
0	On	Off	Authentication
1	Off	Off	Authentication
2	Off	Off	Authentication
3	Off	Off	Authentication
4	Off	Off	Authentication

- # : Display VLANs number.
- **VLAN Mode** : Displays VLAN on/off status. (Please refer to 4.1 VLAN Setup)
- **Authentication** : Displays VLAN# whether enable or disable web authentication.
- **Action** : The function has 2 buttons (Authentication and Dropdown)

### 4.2.1 Enable Authentication function

**Authentication** : By clicking the Authentication button, administrator can enable or disable this function.



- **Authentication :** Administrator can enable or disable authentication function.
- **Multiple Login :** Administrator can set one account to multiple users simultaneously login and the users can set limit.( 0 = not limited)
- **Login Timeout :** After account login for some time no traffic, system will automatic timeout for account. Administrator can enter a time(Minutes).
- **Redirect URL :** After the success of the login, system will redirect to URL. Administrator can enter web site URL.
- **Login URL :** Administrator can set URL for login page.
- **Session Log :** If network have Syslog server. Administrator can to system→management setting IP address for syslog server and enable the function. Account session log will copy to syslog server.

04-30-2018	16:31:31	Local2.Info	192.168.2.254	Jan 1 08:01:36 Session: [danny] tm=1420070496 TCP vlan=0 src=192.168.2.11 sport=44486 dst= dport=443 MAC= :13 auth=64<000> - <b>User account</b>
04-30-2018	16:31:31	Local2.Info	192.168.2.254	Jan 1 08:01:36 Session: [danny] tm=1420070496 TCP vlan=0 src= <b>192.168.2.11</b> sport=45108 dst= dport=443 MAC= auth=64<000> - <b>Used IP address of User</b>
04-30-2018	16:31:30	Local2.Info	192.168.2.254	Jan 1 08:01:35 Session: [danny] tm=1420070495 TCP vlan=0 src=192.168.2.11 sport=48081 dst= dport=443 MAC= auth=64<000> - <b>MAC address of user device</b>
04-30-2018	16:31:30	Local2.Info	192.168.2.254	Jan 1 08:01:35 Session: [danny] tm=1420070495 TCP vlan=0 src=192.168.2.11 sport=42340 dst= dport=443 MAC= auth=64<000>
04-30-2018	16:31:30	Local2.Info	192.168.2.254	Jan 1 08:01:35 Session: [danny] tm=1420070495 TCP vlan=0 src=192.168.2.11 sport=44585 dst= dport=443 MAC= auth=64<000>
04-30-2018	16:31:30	Local2.Info	192.168.2.254	Jan 1 08:01:35 Session: [danny] tm=1420070495 TCP vlan=0 src=192.168.2.11 sport=46136 dst= dport=443 MAC= auth=64<000>
04-30-2018	16:31:30	Local2.Info	192.168.2.254	Jan 1 08:01:35 Session: [danny] tm=1420070495 TCP vlan=0 src=192.168.2.11 sport=44919 dst= dport=443 MAC= auth=64<000>


- **Local User :** Administrator can enable authentication for local user. Create user account can to reference “ **Local User**” setup.
- **RADIUS :** Authentication support remote RADIUS Server. Administrator can enter security information for remote RADIUS Server.

The screenshot shows a 'Radius Setup' configuration window. At the top, there are radio buttons for 'Enable' (selected) and 'Disable'. Below this, several fields are visible: 'Display Name' (Radius User), 'Primary Server IP' (192.168.2.1), 'Secondary Server IP' (Options), 'Authentication Port' (1812), 'Accounting Service' (checkbox, 1813), 'Authentication Type' (radio buttons for PAP and CHAP, with CHAP selected), and 'Secret Key' (Must).

Click “Save” button to save your changes. Then click **Reboot** button to activate your changes.

## 4.2.2 Set Authentication function

**Authentication** : By Clicking the Dropdown button, Administrators can set authentication functions.



### # Guest

Administrator can enable or disable guest authentication. If enabled, the administrator can set guest Count Limit / login time and type and flow control.

Guest

<b>Service</b>	<input checked="" type="radio"/> <b>Enable</b>	<input type="radio"/> <b>Disable</b>
<b>Login Type</b>	<input checked="" type="radio"/> <b>One Time</b>	<input type="radio"/> <b>Multiple Time</b>
<b>Count Limit</b>	<input type="text" value="10"/>	
<b>Login Time</b>	<input type="text" value="10"/>	Minutes
<b>QoS</b>	<input type="radio"/> <b>Enable</b>	<input checked="" type="radio"/> <b>Disable</b>
<b>Upload</b>	<input type="text" value="512"/>	Kbps
<b>Download</b>	<input type="text" value="512"/>	Kbps

- **Service** : Administrator can select enable or disable this function.
- **Login Type** :
  - **One Time**: Login to start counting until the end of time.
  - **Multiple Times**: logout time will stop counting until the next re-login to time start counting.
- **Count Limit**: Administrator can set guest limit.
- **Login Time**: Within a certain timeframe with no traffic, the system will auto logout.
- **QoS**: Administrator can restrict the traffic of guest. Traffic management can set users upload and download traffic.

## # Local User

Administrator can create local user account for web login.


Local User

<b>User Name</b>	<input type="text" value="Local User"/>	
<b>Password</b>	<input type="text" value="(4-32 chars)"/>	<input type="button" value="Add"/>

- **User Name** : Administrator can create users account.
- **Password** : Set account password.

## # OAuth2.0

The OAuth2.0 function supports Facebook and Google by default. Users can add additional OAuth2.0 servers through UI settings.



OAuth 2.0 Provider List <span style="float: right;">Create New Provider</span>			
#	Active	Provider	Action
1	<span style="color: red;">Off</span>	Google	<span style="color: green;">Edit</span> ▼
2	<span style="color: red;">Off</span>	Facebook	<span style="color: green;">Edit</span> ▼

- # : Display items.
- **Active** : Display on/off status for the authentication.
- **Provider** : Display authentication server. The system default use authentication server for Google and Facebook

## Sample for Google OAuth2.0 setup

Please complete the application on the Google website to receive an account ID and password, follow the steps below.

**Step.1** Please go to the **Google Developers Console page** and **create a project**

(Reference <https://developers.google.com/identity/protocols/OAuth2>)

**New Project**



Project name ?

Your project ID will be cerio-aap-login ? [Edit](#)

[Show advanced options...](#)

Create Cancel

**Step.2** Click Credentials to create OAuth client ID in the API manager page.



**Step.3** Select web application in the “Application Type” section and set “Restrictions” URL.

Create client ID

**Application type**

- Web application
- Android [Learn more](#)
- Chrome App [Learn more](#)
- iOS [Learn more](#)
- PlayStation 4
- Other

Create

Cancel

**Name**

**Restrictions**

Enter JavaScript origins, redirect URIs, or both

**Authorized JavaScript origins**

For use with requests from a browser. This is the origin URI of the client application. It can't contain a wildcard (http://\*.example.com) or a path (http://example.com/subdir). If you're using a nonstandard port, you must include it in the origin URI.

**Authorized redirect URIs**

For use with requests from a web server. This is the path in your application that users are redirected to after they have authenticated with Google. The path will be appended with the authorization code for access. Must have a protocol. Cannot contain URL fragments or relative paths. Cannot be a public IP address.

**Step.4** Set Authorized JavaScript origins and Authorized redirect URIs (**important**)

Administrator must set login URL in the device function. After complete set of login URL go to the “Restrictions” function in web page. Follow the steps below to set login URLs

- Setup login URL in the device. Please Click **system** ➔ **Authentication** and enable the function.
- The “Authentication Setup” page to set Login URL

After complete set of login URL go to the “Restrictions” function in web page. Copy and paste the login URL from the system display into the “Restriction” page on the Google Developer website.

- Google Authorized JavaScript origins URL is **http://domain0.login.com** (same as Login URL)
- Google Authorized redirect URIs is **http://domain0.login.com/login/index.cgi?cgi=CALLBACK**

### Authorized JavaScript origins

For use with requests from a browser. This is the origin URI of the client application. It can't contain a wildcard (http://\*.example.com) or a path (http://example.com/subdir). If you're using a nonstandard port, you must include it in the origin URI.

http://domain0.login.com ✕

http://www.example.com

### Authorized redirect URIs

For use with requests from a web server. This is the path in your application that users are redirected to after they have authenticated with Google. The path will be appended with the authorization code for access. Must have a protocol. Cannot contain URL fragments or relative paths. Cannot be a public IP address.

http://domain0.login.com/login/index.cgi?cgi=CALLBACK ✕

http://www.example.com/oauth2callback

**Step.5** After completing the “Restrictions” setup, click the create button. An OAuth Client page will pop-up with your “client ID” and “client secret”. Administrators must copy and paste their client ID and secret into the OAuth 2.0 Setup page in our software UI.

**OAuth client**

Here is your client ID

[REDACTED] googleusercontent.com 📄

Here is your client secret

[REDACTED] :DYwM 📄

OK

OAuth 2.0 Setup
Advanced

**Client ID**

[REDACTED] apps.googleuse

**Client Secret**

[REDACTED] YwM


Save and reboot the AP system, complete the setup.




## Sample for Facebook OAuth2.0 setup

Please complete the application on the Facebook website to receive an account ID and password, follow the steps below.

**Step.1** Please to Facebook developer's page and add a New App



**Step.2** Select WWW function



**Step.3** Administrator must set www for your information.

### Create a New App ID

Get started integrating Facebook into your app or website

#### Display Name

The name of your app or website\*

#### Namespace

\*A unique identifier for your app (optional)

#### Contact Email

Used for important communication about your app


#### Category

Choose a Category ▾


By proceeding, you agree to the [Facebook Platform Policies](#)

Cancel Create App ID

**Step.4** Please click “Setting” and add Platform



**Step.5** Select Platform for “Website”



**Step.6** Enter URL is **http://domain0.login.com/login/index.cgi?cgi=CALLBACK**

Site URL

http://domain0.login.com/login/index.cgi?cgi=CALLBACK

Administrator must set login URL in the device function. After complete set of login URL go to the “Facebook Site URL” function in web page. Follow the steps below to set login URLs

- Setup login URL in the device. Please Click **system**➔**Authentication** and enable the function.
- The “**Authentication Setup**” page to set Login URL

After complete set of login URL go to the “Facebook Site URL” function in web page. Copy and paste the login URL from the system display into the “Site URL” page on the Facebook website.

**Step.7** Click Advanced function to enable the “Native or desktop app?” and “Is App Secret embedded in the client?”

**Step.8** After completing the “Facebook Site URL” setup. Administrators must copy and paste their App ID and App secret into the OAuth 2.0 Setup page in our software UI.

OAuth 2.0 Setup
Advanced

Client ID


Client Secret

**Notice**

Client ID and Client Secret setup by third parties such as Facebook and Google are subject to change. The instructions above follow the 2016 setup procedure. Any future changes to the Facebook/Google process may lead to our instructions becoming invalid.

## # POP3/IMAP Server

The purpose of this integrated function is to allow clients to link a POP3 server for receiving emails from a remote server.



POP3/IMAP Server

Service  Enable  Disable

POP3/IMAP Settings

Display Name

Mode  POP3  IMAP

Host

Port  Port

Connect Type  ▼

POP3/IMAP Server Test

EMAIL

Password  Test

- **Service:** Administrator can choose Enable or Disable the PoP3 authentication.
- **Display Name :** Set the “Display Name” based on the appropriate POP3 user or client.
- **Host :** Define the desired Host server name.
- **Port :** Input the proper port number for the corresponding server.

- **Connect Type** : Select the Connect type with options of “STARTTLS”, “SSL/TTL”, or “None”.
- **POP3 Server Test** : Use this tool to test if the POP3 server is operating correctly with your selected email

## # Customize Page

This function is to customize the user Login Page. This supports Multiple Language and allows comprehensive customization through HTML editing.

### Page Setup

- **Template** : Administrator can select Enable or disable.
  - Select enable to active default Login Page

- Select disable to active HTML Source code window for customization

```

Customize HTML Source code

<html>
  <head>
    <title>Hotspot</title>
    <script src="/javascripts/login.js" charset="utf-8" type="text/javascript"></script>
  </head>
  <body>
    <div class="container"></div>
  </body>
</html>
    
```

**Sample:** See sample login page below that is customized by html coding (*sample login page html code templates are available on Cerio website*)



The following function uses the enabled Template

- **Multiple Language :** Administrator can select enable or disable multiple language for login page. Administrator must to Language function create new language.
- **Page Color Setup :** Administrator can change the login page color.

## # Language

Administrator can create other language for login page.

Language List <span style="float: right;">Create New Language</span>			
#	Default	Language	Action
1	★	English	Edit

Click “Create New Language” button go to add or edit language for login page.

**Language**

Language:

Default Language:  Enable  Disable

- Language: Set description of language.
- Default Language: Display default language.

## # Walled Garden

This function provides certain free services or advertisement web pages for users to access the websites listed before login and authentication. User without the network access right can still have a chance to experience the actual network service free of charge in Walled Garden URL list.

**Walled Garden**

Display Name:

IP Address/Domain:

Full URL:  Add

- **Display Name:** Set name of Website.
- **IP Address/Domain:** Set IP or Domain of the Open the website.
- **Full URL:** Set full website name.

## # Privilege Address

This function provides local device can access Internet without authentication. If there are some workstations belonging NGS Access Point that need to access to network without authentication, enter the IP or MAC address of these workstations in this list.

Privilege Address

Device Name	<input type="text" value="(4-32 characters)"/>
IP Address	<input type="text"/>
MAC Address	<input type="text"/> <input type="button" value="Add"/>

- **Device Name:** Enter Device or Users Name.
- **IP Address:** Enter used IP Address of Device or Users PC.
- **MAC Address:** Enter MAC Address of Device or Users PC.

Click **“Save”** button to save your changes. Then click Reboot button to activate your changes..

## # Profile

Administrator can backup current authentication configuration and login page for HTML Source code. But also can recover.

VLAN Profile

Download Profile Setting	<input type="button" value="Download"/>
Upload Profile Setting	<input type="button" value="Choose File"/> No file chosen <input type="button" value="Upload"/>

---



VLAN Customize Page

Download Customize Page	<input type="button" value="Download"/>
Upload Customize Page	<input type="button" value="Choose File"/> No file chosen <input type="button" value="Upload"/>

Click **“Save”** button to save your changes. Then click **Reboot** button to activate your changes.



## 4.3 RADIUS Server





Radius Server	
Service	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Radius Port	<input type="text" value="1812"/>
Radius Secret	<input type="text" value="(4-32 chars)"/>

- **Service** : Administrator can select Enable or disable the function.
- **Radius** : Administrator must to set remote RADIUS Server use Port.
- **Radius Secret** : Administrator must to set remote RADIUS Server use Key.

Click “**Save**” button to save your changes. Then click **Reboot** button to activate your changes.

## 4.4 RADIUS Account Setup

When enabled RADIUS Server, administrator can add RADIUS account and password in the function. But also can recover or backup the RADIUS account. Account can create 50 users limit



**Radius User**

**User Name**

**Password**  Add

**Export/Import Users**

**Export User File** Export

**Import From PC**  Import


- **User Name** : Create users name for RADIUS account.
- **Password** : Enter password for user name.
- **Export User File** : Administrator can export account list in RADIUS Server.
- **Import From PC** : Administrator can import account list to the RADIUS Server.

Click **“Save”** button to save your set function. Then click Reboot button to activate your changes.

## 4.5 Wireless Configuration

This wireless functions administrator can set radio 2.4/5G application of the Access Point.

### 4.5.1 Radio 0 Setup (2.4G)



**General Setup**

**MAC Address**

**Station Mode**  Enable  Disable

**Country**

**Band Mode**

**Auto Channel**  Enable  Disable

**Channel**

**Tx Power**


**Slot Time**  Distance

**ACK Timeout**

- **MAC Address:** Display 2.4G WiFi MAC address.
- **Country:** Administrator can select country: US or EU or Taiwan.
- **Band Mode:** Administrator can select 802.11b/g/n for the 2.4G Band.
- **Auto Channel:** Administrator can Enable or Disable the function. If disabled, the WiFi channel will be fixed to the manually selected channel.
- **Channel:** Administrator can select 1 to 11 CH. The Channel settings can be changed in “HT Physical Mode” → “Extension Channel” can select **Upper** or **Lower** channels.

Extension Channel
 Upper
 Lower

- **Tx Power:** Administrator can control the WiFi Tx output power. The power Max. Level 9.
- **Slot Timeout :** You can enter the slot time value here. When the distance is long or short, the waiting time for packet transmission will be adjusted fast and slow.  
**Distance:** When the "Distance" button is clicked, the point-to-point bridge distance can be entered. The system will automatically calculate the ideal reference value for the Slot Time and ACK Timeout. The input distance is calculated in units (meters).
- **ACK Timeout :** When waiting for the "ACKnowledgment frame" interval is too long to be received, the ACK will be retransmitted. A higher ACK Timeout will reduce packet loss, but the transmission efficiency will be poor.



Setting Slot Time and ACK Timeout can strengthen the long-distance connection. Changing the value can optimize the setting. If the value is too low, the length transmission will be reduced. If the value is too high, there may be disconnection.

## HT Physical Mode

☰ HT Physical Mode

**TX/RX Stream**

**Channel BandWidth**


**Extension Channel**
 Upper
 Lower

**MCS**

**Short GI**
 Enable
 Disable

**Aggregation**
 Enable
 Disable



- **TX/RX Stream:** The CenOS 5.0 AP utilizes 2 antennas and support 2TX/2RX streams. Administrator can select 1 or 2 TX/RX. The default is 2TX/2RX.
- **Channel Bandwidth:** The "20/40" MHz option is usually best. The other option is available for special circumstances.



**Notice** *This product has a built-in 2x2 (2T2R) antenna for 2.4Ghz, which has been matched with the default setting of 2T2R. If there is no special demand, please keep this default setting .*

- **Extension Channel:** Sets channel select to Upper or Lower. The Upper supports 1 to 7 range CH and Lower supports 5 to 11 range CH.
- **MCS:** This parameter represents transmission rate. By default (Auto) the fastest possible transmission rate will be selected. You have the option of selecting the speed if necessary.
- **Shout GI:** Short Guard Interval is “Enabled” by default to increase throughput. However, it can also increase error rate in some installations, due to increased sensitivity to radio-frequency reflections. Select the option that works best for your installation.
- **Aggregation:** By default, it's “Enabled”. Select “Disable” to deactivate Aggregation. A part of the 802.11n standard (or draft-standard), it allows sending multiple frames per single access to the medium by combining frames together into one larger frame. It creates the larger frame by combining smaller frames with the same physical source and destination end points and traffic class (i.e. QoS) into one large frame with a common MAC header.


## 4.5.2 Radio 1 Setup(5G)

- **MAC Address:** Display 5G WiFi MAC address.
  - **Country:** Administrator can select country: US or EU or Taiwan.
  - **Band Mode:** Administrator can select 5G Band for 802.11a/n or 802.11ac. The default is 802.11ac
  - **Auto Channel:** Administrator can Enable or Disable the function. If select disabled function the WiFi channel can be manually fixed.
  - **Channel:** Supports US and EU country 5G Channel standards.
  - **Tx Power:** Administrator can control the WiFi Tx output power. The power Max. Level 9.
  - **Slot Timeout :** You can enter the slot time value here. When the distance is long or short, the waiting time for packet transmission will be adjusted fast and slow.
- Distance:** When the "Distance" button is clicked, the point-to-point bridge distance can be entered.

The system will automatically calculate the ideal reference value for the Slot Time and ACK Timeout. The input distance is calculated in units (meters).

- **ACK Timeout** : When waiting for the "ACKnowledgment frame" interval is too long to be received, the ACK will be retransmitted. A higher ACK Timeout will reduce packet loss, but the transmission efficiency will be poor.




**Notice** *Setting Slot Time and ACK Timeout can strengthen the long-distance connection. Changing the value can optimize the setting. If the value is too low, the length transmission will be reduced. If the value is too high, there may be disconnection.*

## HT Physical Mode

☰ HT Physical Mode

<b>TX/RX Stream</b>	2T2R	▼
<b>Channel BandWidth</b>	80	▼
<b>Short GI</b>	<input checked="" type="radio"/> <b>Enable</b>	<input type="radio"/> <b>Disable</b>
<b>Aggregation</b>	<input checked="" type="radio"/> <b>Enable</b>	<input type="radio"/> <b>Disable</b>

- **TX/RX Stream**: Administrator can select 1 or 2 TX/RX. The default is 2TX/2RX.




**Notice** *This product has a built-in 2x2 (2T2R) antenna for 5Ghz, which has been matched with the default setting of 2T2R. If there is no special demand, please keep this default setting .*

- **Channel Bandwidth**: The "20/40 and 802.11ac 80" MHz option is usually the best. The other option is available for special circumstances.
- **Short GI**: Short Guard Interval is "Enabled" by default to increase throughput. However, it can also increase error rate in some installations, due to increased sensitivity to radio-frequency reflections. Select the option that works best for your installation.
- **Aggregation**: By default, it's "Enable". Select "Disable" to deactivate Aggregation. A part of the 802.11n standard (or draft-standard). It allows sending multiple frames per single access to the medium by combining frames together into one larger frame. It creates the larger frame by combining smaller frames with the same physical source and destination end points and traffic class (i.e. QoS) into one large frame with a common MAC header.

Click "Save" button to save your set function. Then click "Reboot" button to activate your changes.

## 4.5.3 Advanced Setup



- **Beacon Interval:** Beacon Interval is in the range of **40~3500** and set in unit of *millisecond*. The default value is **100** msec.

Access Point (AP) in IEEE 802.11 will send out a special approximated 50-byte frame, called “Beacon”. Beacon is broadcast to all the stations, provides the basic information of AP such as SSID, channel, encryption keys, signal strength, time stamp, support data rate.

All the radio stations received beacon recognizes the existence of such AP, and may proceed next actions if the information from AP matches the requirement. Beacon is sent on a periodic basis, the time interval can be adjusted.

By increasing the beacon interval, you can reduce the number of beacons and associated overhead, but that will likely delay the association and roaming process because stations scanning for available access points may miss the beacons. You can decrease the beacon interval, which increases the rate of beacons. This will make the association and roaming process very responsive; however, the network will incur additional overhead and throughput will go down.

- **DTIM Interval:** The DTIM interval is in the range of **1~255**. The default is **1**.  
DTIM is defined as *Delivery Traffic Indication Message*. It is used to notify the wireless stations, which support power saving mode, when to wake up to receive multicast frame. DTIM is necessary and critical in wireless environment as a mechanism to fulfill power-saving synchronization.  
A DTIM interval is a count of the number of beacon frames that must occur before the access point sends the buffered multicast frames. For instance, if DTIM Interval is set to 3, then the Wi-Fi clients will expect to receive a multicast frame after receiving three Beacon frame. The higher DTIM interval will help power saving and possibly decrease wireless throughput in multicast applications.

- **Fragmentation Threshold:** Fragmentation Threshold is one more parameter which is given in all stations and Access points. Fine tuning Fragmentation Threshold parameter can result in good throughput but not using it properly can result in low throughput. In simple words it does the same thing which MTU do in Ethernet. Both are different parameters but the work done is same, it fragments the data packets.  
Fragmentation threshold will be used when we have more data packet size to be transmitted and we have less fragment threshold value. Let's say from Ethernet we have to send 1400 byte packet but the fragmentation threshold is set as 400. In this case when the packet is to be transmitted on air it will fragment the packet in to 4 small packet 400+400+400+200 and send on air. This includes MAC header+ frame body and CRC so 400 byte will be in total including headers. This helps in increasing the throughput. The default is 2346.
- **RTS Threshold:** RTS Threshold is in the range of **1~2347** byte. The default is **2347** byte.  
The main purpose of enabling RTS by changing RTS threshold is to reduce possible collisions due to hidden wireless clients. RTS in AP will be enabled automatically if the packet size is larger than the Threshold value. By default, RTS is disabled in a normal environment supports non-jumbo frames.
- **Short Preamble:** By default, this function is **"Enabled"**. **Disabling** will automatically use the Long 128-bit Preamble Synchronization field. The preamble is used to signal "here is a train of data coming" to the receiver. The short preamble provides 72-bit Synchronization field to improve WLAN transmission efficiency with less overhead.
- **IGMP Snooping:** The process of listening to Internet Group Management Protocol (IGMP) network traffic. The feature allows a network switch to listen in on the IGMP conversation between hosts and routers. By listening to these conversations the switch maintains a map of which links need which IP multicast streams. Multicasts may be filtered from the links which do not need them and thus controls which ports receive specific multicast traffic.
- **Greenfield:** In wireless WLAN technology, greenfield mode is a feature of major components of the 802.11n specification. The greenfield mode feature is designed to improve efficiency by eliminating support for 802.11b/g devices in an all draft-n network. In greenfield mode the network can be set to ignore all earlier standards.
- **RF on/off by schedule:** Administrator can apply Time Policy to on or off wireless signal.
- **Location Tracking Log:** The system can detect the signal strength of the wireless client to determine the location of the Access Point and send to database.

```
Jan 1 08:28:00 Wifilogd: tm=1420072080 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=04:7:08:11:19 rssi=-67
Jan 1 08:27:00 Wifilogd: tm=1420072020 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=04:7:08:11:19 rssi=-68
Jan 1 08:26:00 Wifilogd: tm=1420071960 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=04:7:08:11:19 rssi=-67
```

Click **"Save"** button to save your set function. Then click **"Reboot"** button to activate your changes.

## 4.5.4 WMM Setup

This affects traffic flowing from the access point to the client station.

Configuring QoS options consists of setting parameters on existing queues for different types of wireless traffic. You can configure different minimum and maximum wait times for the transmission of packets in each queue based on the requirements of the media being sent. Queues automatically provide minimum transmission delay for Voice, Video, multimedia, and mission critical applications, and rely on best-effort parameters for traditional IP data.

As an Example, time-sensitive Voice & Video, and multimedia are given effectively higher priority for transmission (lower wait times for channel access), while other applications and traditional IP data which are less time-sensitive but often more data-intensive are expected to tolerate longer wait times.

Please click on **Wireless -> WMM Setup**

WMM Parameters of Access Point					
AC Type	CWmin	CWmax	AIFS	TxOp Limit	No ACK Policy bit
AC_BE(0)	4	6	3	0	<input type="checkbox"/>
AC_BK(1)	4	10	7	0	<input type="checkbox"/>
AC_VI(2)	3	4	1	3008	<input type="checkbox"/>
AC_VO(3)	2	3	1	1504	<input type="checkbox"/>

WMM Parameters of Station					
AC Type	CWmin	CWmax	AIFS	TxOp Limit	ACM bit
AC_BE(0)	4	10	3	0	<input type="checkbox"/>
AC_BK(1)	4	10	7	0	<input type="checkbox"/>
AC_VI(2)	3	4	2	3008	<input type="checkbox"/>
AC_VO(3)	2	3	2	1504	<input type="checkbox"/>



➤ **AC Type :**

Queue	Data Transmitted AP to Clients	Priority	Description
AC_BK	Background	Low	High throughput. Bulk data that requires maximum throughput and is not time-sensitive is sent to this queue (FTP data, for example).
AC_BE	Best Effort	Medium	Medium throughput and delay. Most traditional IP data is sent to this queue.
AC_VI	Video	High	Minimum delay. Time-sensitive video data is automatically sent to this queue.
AC_VO	Voice	High	Time-sensitive data like VoIP and streaming media are automatically sent to this queue.


- **CWmin:** Minimum Contention Window. This parameter is input to the algorithm that determines the initial random backoff wait time ("window") for retry of a transmission. The value specified here in the Minimum Contention Window is the upper limit (in milliseconds) of a range from which the initial random backoff wait time is determined.
- **CWmax:** Maximum Contention Window. The value specified here in the Maximum Contention Window is the upper limit (in milliseconds) for the doubling of the random backoff value. This doubling continues until either the data frame is sent or the Maximum Contention Window size is reached. Once the Maximum Contention Window size is reached, retries will continue until a maximum number of retries allowed is reached. Valid values for the "cwmax" are 1, 3, 7, 15, 31, 63, 127, 255, 511, or 1024. The value for "cwmax" must be higher than the value for "cwmin". ◦
- **AIFS :** The Arbitration Inter-Frame Spacing Number specifies a wait time (in milliseconds) for data frames ◦
- **TxOP Limit:** Transmission Opportunity is an interval of time when a WME AP has the right to initiate transmissions onto the wireless medium (WM). This value specifies (in milliseconds) the Transmission Opportunity (TXOP) for AP; that is, the interval of time when the WMM AP has the right to initiate transmissions on the wireless network. ◦
- **ACM bit:** Admission Control Mandatory, ACM only takes effect on AC\_VI and AC\_VO. When you do not click Checkbox, it means that the ACM is controlled by the connecting AP. If you click Checkbox, it means that the Client is in charge ◦
- **No ACK policy bit:** Acknowledgment Policy, WMM defines two ACK policies: **Normal ACK** and **No ACK**. Click "Checkbox" indicates "No ACK"  
When the no acknowledgement (No ACK) policy is used, the recipient does not acknowledge received packets during wireless packet exchange. This policy is suitable in the environment where communication quality is fine and interference is weak.

While the No ACK policy helps improve transmission efficiency, it can cause increased packet loss when communication quality deteriorates. This is because when this policy is used, a sender does not retransmit packets that have not been received by the recipient. When the Normal ACK policy is used, the recipient acknowledges each received unicast packet.

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 4.5.5 WDS Setup

Please click on Wireless -> WDS Setup



When the WDS function is enabled, it can be set to use Radio 0 (2.4G) for WDS or Radio 1 (5G) for WDS, etc., and a maximum of 24 groups can be set up to bridge to 2.4G + 5G + 5G. In WDS The function supports VLAN tag transmission. If there is a tag set in the network domain, WDS can bring multiple groups of tags to another bridge endpoint.

**WDS Setup**

WDS Setup  Enable  Disable

Radio0 ESSID: default\_wds0

Radio1 ESSID: default\_wds1

Security Type: Disable

PassPhrase:

---

**WDS Client Setup**

Radio 0		Radio 1	
Enable	MAC Address	Enable	MAC Address
<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>	
<input type="checkbox"/>		<input type="checkbox"/>	

**MAC Address**

Radio 0: 8c:4d:ea:05:1c:75


Radio 1: 8c:4d:ea:05:1c:75

---

**VLAN Setup**

VLAN#	Radio 0			Radio 1		
	Native	TAG	TAG ID	Native	TAG	TAG ID
VLAN 0	<input checked="" type="radio"/>	<input type="checkbox"/>		<input checked="" type="radio"/>	<input type="checkbox"/>	
VLAN 1	<input type="radio"/>	<input type="checkbox"/>	101	<input type="radio"/>	<input type="checkbox"/>	101
VLAN 2	<input type="radio"/>	<input type="checkbox"/>	102	<input type="radio"/>	<input type="checkbox"/>	102
VLAN 3	<input type="radio"/>	<input type="checkbox"/>	103	<input type="radio"/>	<input type="checkbox"/>	103
VLAN 4	<input type="radio"/>	<input type="checkbox"/>	104	<input type="radio"/>	<input type="checkbox"/>	104
VLAN 5	<input type="radio"/>	<input type="checkbox"/>	105	<input type="radio"/>	<input type="checkbox"/>	105
VLAN 6	<input type="radio"/>	<input type="checkbox"/>	106	<input type="radio"/>	<input type="checkbox"/>	106
VLAN 7	<input type="radio"/>	<input type="checkbox"/>	107	<input type="radio"/>	<input type="checkbox"/>	107
VLAN 8	<input type="radio"/>	<input type="checkbox"/>	108	<input type="radio"/>	<input type="checkbox"/>	108
VLAN 9	<input type="radio"/>	<input type="checkbox"/>	109	<input type="radio"/>	<input type="checkbox"/>	109
VLAN 10	<input type="radio"/>	<input type="checkbox"/>	110	<input type="radio"/>	<input type="checkbox"/>	110
VLAN 11	<input type="radio"/>	<input type="checkbox"/>	111	<input type="radio"/>	<input type="checkbox"/>	111
VLAN 12	<input type="radio"/>	<input type="checkbox"/>	112	<input type="radio"/>	<input type="checkbox"/>	112

- **WDS Setup:** Administrator can select Enable or Disable.
- **Security Type:** Enable or Disable AES 128bit encryption function.
- **Pass Phrase :** AES encryption custom key can input 0 ~ 9 numbers or A ~ Z uppercase and lowercase English format, it can support 8 ~ 32 characters key encryption algorithm in each WDS connecting each other with secure encrypted transmission.
- **MAC Address :** Enter the MAC address of the other party's host to agree to accept the connection.
- **WDS Client Setup:** Administrator can used Radio 0(2.4G) or Radio 1(5G) for WDS Links. A Single Radio supports up to 8 WDS links.



**Notice**

*WDS considerations*

1. *When two wireless APs want to use WDS connection, the channels of the two must be the same.*
2. *If the two base AP stations are A and B, the WDS Client Setup of station A needs to set the wireless MAC address of station B, and the WDS Client Setup of station B needs to set the wireless MAC address of station A.*
3. *If tags must be used in the architecture, the APs on both sides can select multiple sets of tags in the virtual network settings.*
4. *WDS encryption setting is by optional use.*


- **VLAN Setup:** The WDS aisle support Multi-tag VALN

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 4.5.6 WDS Status

Displays 2.4G and 5G radio WDS link status through MAC and Date (TX/RX)

Please click on **Wireless -> WDS status**



Radio0 Client		
MAC Address	Rate(RX/TX)	RSSI
-	-	-

Radio1 Client		
MAC Address	Rate(RX/TX)	RSSI
-	-	-

- **MAC Address** : Display connected MAC Address. °
- **Rate(TX/RX)** : Display Tx/Rx rate of the point to point °
- **RSSI**: Display signal connection value of RSSI


Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 5. CAP Mode

The CAP mode itself isn't Access Point. This mode is primarily to control all the managed AP. The following describes setup function in system menu

### 5.1 Change Setup mode


If the administrator needs to switch to CAP mode, Please click "System"-> " Mode Setup " to change CAP mode.



*Please note that the LAN IP addresses in each mode are different from each other and will not continue. For the first time after switching modes, always perform access management on the LAN default IP address of 192.168.2.254*

### 5.2 VLAN Setup

Start by setting the AP's (LAN) IP address, Please Click " System " → " VLAN Setup "



Setup "Control AP" of LAN or VLAN IP Address, Gateway, DNS and Ethernet Tag etc.

**This VLANs support max 16 IEEE 802.1q tag VLANs.**

#	Status	Flag	IP Address	Netmask	Action
0	On	Native ETH0	192.168.2.254	255.255.255.0	Network
1	Off	ETH0.101	192.168.101.254	255.255.255.0	Network
2	Off	ETH0.102	192.168.102.254	255.255.255.0	Network
3	Off	ETH0.103	192.168.103.254	255.255.255.0	Network
4	Off	ETH0.104	192.168.104.254	255.255.255.0	Network
5	Off	ETH0.105	192.168.105.254	255.255.255.0	Network
6	Off	ETH0.106	192.168.106.254	255.255.255.0	Network
7	Off	ETH0.107	192.168.107.254	255.255.255.0	Network

<b>Gateway</b> Default Gateway: <input type="text" value="192.168.2.1"/>	<b>DNS</b> DNS1: <input type="text" value="192.168.2.1"/> DNS2: <input type="text"/>
---	--


- **#** : Display VLAN No.
- **VLAN Mode** : Display on /off line status for the VLAN mode
- **IP Address** : Display IP address for the VLAN mode.
- **NetMask** : Display netmask for the VLAN mode.
- **Action** : Administrator can set VLAN IP 、 Radio 2.4 or 5G on/off 、 Spanning tree 、 IAPP and VLAN tag.

<b>VLAN Setup</b> VLAN Mode: <input checked="" type="radio"/> Enable <input type="radio"/> Disable	<b>Management</b> 802.1d Spanning Tree: <input type="radio"/> Enable <input checked="" type="radio"/> Disable
<b>IP Setup</b> IP Address: <input type="text" value="192.168.2.254"/> Netmask: <input type="text" value="255.255.255.0"/>	<b>ETH0 VLAN Tag Setup</b> ETH0: <input checked="" type="radio"/> Enable <input type="radio"/> Disable VLAN TAG: <input type="checkbox"/> 1-4096

- **VLAN Mode** : Administrator can Enable or disable the VLAN function.

There must always be at least one VLAN enabled. If the administrator disables all the VLANs, he/she will not be able to login to the manager page. The administrator must then reset to default.

- **IP setup** : Administrator can set the VLAN IP address and NetMask or disable IP.
- **802.1d Spanning Tree** : The spanning tree network protocol provides a loop free topology for a bridged LAN between LAN interface and 8 WDS interfaces from wds0 to wds7. The Spanning Tree Protocol, which is also referred to as STP, is defined in the IEEE Standard 802.1d.



- **ETH0** : Administrator select Enable/disable the Ethernet port.
- **VLAN Tag** : Administrator can set Tag ID for the Ethernet port.

➤ **Set Gateway / DNS address functions.**



- **Gateway:** The default Gateway IP Address is 192.168.2.1, Please check your Gateway IP and change.
- **DNS:** Check either “No Default DNS Server” or “Specify DNS Server IP” button as desired to set up the system DNS.
  - ✓ **Primary:** The IP address of the primary DNS server.
  - ✓ **Secondary:** The IP address of the secondary DNS server.

Click “**Save**” button to save your set function. Then click “**Reboot**” button to activate your changes.

## 5.3 AP Control

When CenOS5.0 AP changes to CAP mode, Administrator can use AP Control functions to centralize management of APs in the network architecture. AP control Setting functions have “Scan Device”, “Batch Setup”, “AP Setup”, “Group / Map setup” and Authentication Profile setup etc..

Please click “**AP Control**” to enter AP Management settings

### # Centralized Management APs operating Instructions:

- 1) Click “**Scan Device**” to discover Access Points in the network architecture.
- 2) Set IP address for all managed Access Points and reboot managed Access Points.
- 3) Re-Scan managed APs and Import to databases.
- 4) Centralize managed AP settings by clicking “**AP control**” → “**Batch setup**”
- 5) After the setup is complete for managed APs function, administrator must reboot all managed APs.

## 5.3.1 Scan Device

This management page can discover all managed APs in the network. Administrator can set IP address / Password and VLAN tag for managed APs. After the setup is complete, Administrator must import all managed APs to databases.

**Filter Device**

VLAN#

Default Password

Sort

- **VLAN#** : Administrator can select VLAN network to discovery managed Aps
- **Default Password**: Set login system password by managed Aps.
- **Sort**: Administrator can select discovery managed Aps Type. (IP or MAC)
- 

#	<input type="checkbox"/>	IP Address	MAC Address	Password	Host Name	F/W Version	F/W Date	IP Address	Netmask	Action
1	<input type="checkbox"/>	192.168.2.253	8c-4d-ea-04-d0-6e	.....	CW-400NAC-E1	Pme-CPE-ACS V1.1.0	2016/05/06 09:19:35	<input type="text" value="192.168.2.253"/>	<input type="text" value="255.255.255.0"/>	<input type="button" value="Info"/>

- **#** : Display managed APs items.
- **Device** : Administrator can select all or single for managed Aps.
- **IP Address** : Display IP address for managed AP.
- **MAC Address** : Display MAC address for managed AP.
- **Host Name** : Display host name for managed AP.
- **F/W Version** : Display firmware version for managed AP.
- **F/W Date** : Display firmware Release date for managed AP.
- **IP Address** : Administrator can set single IP address for Managed AP.
- **Netmask** : Administrator can set single Netmask for Managed AP.
- **Default** : Administrator click the button will can reset to default for select managed APs.

**Update IP Address & Netmask**

Control Port

VLAN TAG

IP Address

Netmask




- **Control Port** : Administrator can change VLAN network for managed APs.
- **VLAN TAG** : Administrator can set VLAN TAG ID for managed APs.
- **IP Address** : Administrator can set IP address for managed APs, the IP address is auto-incrementally.
- **NetMask** : Administrator can set NetMask for managed APs.


When the setting managed APs is completed, please click Apply & Reboot button to complete the setup process.

### 5.3.2 Batch Setup

The AP control function supports centralized configuration of managed APs. Administrator can change VLAN network / Group and batch setup for managed APs.



- **LAN** : When VLAN Tag function is enabled (please refer to 4.1 System VLAN Setup), administrator can change VLAN tag for managed APs.
- **Group** : When AP Groups are created (please refer to 7.2.4 Group setup), Administrators can select and change group settings of managed APs.
- **Batch Setup** : Administrator can centralize setting changes for managed APs.



- **VLAN Setup** : Administrator can set VLAN Tag, IP address and Wi-Fi on/off for the managed APs.

VLAN Setup
Apply

**VLAN** VLAN 0

**VLAN Mode**  Enable  Disable

**Access Point 0**  Enable  Disable

**Access Point 1**  Enable  Disable

**802.1d Spanning Tree**  Enable  Disable

**Control Port**  Enable  Disable

**IAPP** Disable

- ✓ **VLAN** : The function can select VLAN (please refer to “Configure VLAN Setup”) for managed APs.
- ✓ **VLAN Mode** : Administrator can enable or disable VLAN mode of the managed APs.
- ✓ **Access Point0/1** : Administrator can enable or disable 2.4G or 5G radio of the managed APs. (Access Point 0 is radio 2.4G, Access Point 1 is radio 5G)
- ✓ **802.1d Spanning Tree** : Administrator can enable or disable the function.( please refer to “Configure Network → 802.1d Spanning Tree”)
- ✓ **Control Port** : The function administrator can enable or disable of the managed APs (please refer to “Configure Network → Control Port”)
- ✓ **IAPP** : The function administrator can enable or disable of the managed APs (Please refer to “Configure Network → IAPP”)

IP Setup

**Apply**  Enable  Disable

**IP Mode**  Enable  Disable

**IP Address** 192.168.2.10

**Netmask** 255.255.255.0

ETH0 VLAN Tag Setup

**ETH0**  Enable  Disable

**VLAN TAG**  1-4096

ETH1 VLAN Tag Setup

**ETH1**  Enable  Disable

**VLAN TAG**  1-4096


- ✓ **IP Setup** : Administrator can set IP address and Netmask of the managed APs.
- ✓ **ETH0/1 VLAN Tag Setup** : Administrator can set VLAN Tag or disable VLAN function

of the managed APs.

- **Authentication Profile** : After creating Profiles, See: “Authentication Profile” users can conveniently apply Authentication profiles
- **Gateway & DNS**: Setting Gateway and DNS for managed APs.
- **Time Server**: Setting System Time for managed APs. (Please refer to Configure Time Server)
- **Management Setup**: Setting system name/ system login port and system log server service for managed APs. (Please refer to “system management”)
- **Wireless Batch Setup**: Setting Wi-Fi configurations for managed APs. (Please refer to “Wireless Basic Setup”)
- **Wireless Advanced Setup**: Setting Wi-Fi Advanced settings for managed APs. (Please refer to “Wireless Advanced Setup”)
- **VAP Setup** : Wi-Fi SSID / channel or security settings for managed APs. (Please refer to “Configure Radio 0/1”)
- **Upgrade via TFTP Server**: Administrator can centrally upgrade firmware via TFTP Server for the managed APs.
- **Upgrade via HTTP Server**: Administrator can centrally upgrade firmware via HTTP Server for the managed APs.
- **Reboot**: Administrator can reboot managed APs.

### 5.3.3 AP Setup

Administrator can monitor statuses and modify managed APs information.



The screenshot shows a web interface with two main sections: 'VLAN List' and 'Device List'. The 'VLAN List' section has a dropdown menu for 'VLAN' currently set to 'All'. The 'Device List' section contains a table with columns for VLAN#, Device, Status, System Name, IP Address, MAC Address, Uptime, and Action. There are buttons for 'Choice All', 'Delete', and 'Refresh' above the table. The table has one row for 'VLAN0' with a status icon, system name 'GW-400NAG-E1', IP '192.168.2.253', MAC '8a:4d:ea:04:d0:6e', and uptime '03:43:28'. An 'Action' column for this row contains a 'Setup' button.

VLAN#	Device	Status	System Name	IP Address	MAC Address	Uptime	Action
VLAN0	<input type="checkbox"/>		GW-400NAG-E1	192.168.2.253	8a:4d:ea:04:d0:6e	03:43:28	Setup

- **VLAN** : Select desired VLAN for AP setup
- **Setup** : Administrator can modify IP addresses, system login passwords, and web login port for managed APs. If administrator has change AP devices, administrator can modify MAC address of the new managed AP.

**Device Setup**

VLAN:

Group:

IP Address:

MAC Address:

Password:

HTTP Port:

### 5.3.4 Group Setup

Administrator can create Groups within the same VLAN.

**VLAN List**

VLAN:

---

**Group List**

#	VLAN	Name	Description	Action
-	-	-	-	-

- **VLAN** : Select VLAN.
- **Create New Group** : Click the button to create a new AP Group

**Group List**

#	VLAN	Name	Description	Action
1	VLAN 0	test	Office group	<input type="button" value="Device"/>

- ✓ **Device button** : Administrator can select managed APs and import them into the Group.

### 5.3.5 Map Setup

The Map Setup feature allows administrators to upload a floor plan image to a web server, then use the image URL to import the map into the AP user interface. Once the image is uploaded, administrators can use the Map Setup function to map out the locations of the AP network.

**Map List**

#	Name	Description	Action
1	1F_plan	Location Map for man...	<input type="button" value="View"/>

- **reate New Map** : Click the button to create map.

**Map Setting**

Map Name

Image URL


Description

Image

- **Map Name** : Enter map name.
- **Image URL** : Paste Map image url
- **Description** : Enter the description for the map.

After the Map URL setup confirmation, please reboot the system.

**View** : Once the Map is created and properly in the Map List, administrators can click the “Layout” button in the action tab to map out the AP network. Managed APs will appear in the “Device List” section of the layout page. Administrators can simply drag the AP (IP Address) to the correct installation location.



Map List <span style="float: right;"><input type="button" value="Create New Map"/></span>			
#	Name	Description	Action
1	1F_plan	Location Map for man...	<input type="button" value="View"/>

**View** : Once complete, administrators can click the “View” button to monitor AP statuses and locations.



### 5.3.6 Authentication Profile


Administrator can pre-set authentication conditions in the profile, the authentication set can refer “Authentication”.

Authentication Profile List <span style="float: right;">Create New Profile</span>					
#	Name	Description	Authentication	Edit	Action
1	Authentioatlon-test1		Off	Authentication	Setup

- **Create New Profile** : Administrator can create authentication profile.
- **Edit** : Authentication Click the Authentication button to Enable or Disable authentication function. For more details, refer to “**Authentication**”.
- Authentication Click Dropdown to set authentication functions. Refer to “**Authentication**” dropdown functions.
- **Action**: Setup The button can modify or delete for the authentication profile.

### 5.3.7 Status

Administrator can monitor Tx/Rx flow information, show online users and check system CPU / Memory information and on/off line for the managed APs. The information data display support graphical interface.




## 6. Client Bridge Mode

When Client Bridge is chosen, the system can be configured as a Client Bridge and support Repeater AP function. This can setup VLAN and DHCP server in the system menu.

### 6.1 Change Setup mode

If the administrator needs to switch to Client Bridge mode, Please click "System"-> " Mode Setup " to change Client Bridge mode.




**Notice** *Please note that the LAN IP addresses in each mode are different from each other and will not continue. For the first time after switching modes, always perform access management on the LAN default IP address of 192.168.2.254*

This section provides detailed explanation for users to configure in the Client Bridge Mode and Repeater AP function with help of illustrations.

### 6.2 Configure LAN Setup

Here are the instructions for how to setup the local IP Address and Netmask. Please click on **System -> LAN** and follow the below setting.



<b>Ethernet Connection Type</b> Mode <input checked="" type="radio"/> Static IP <input type="radio"/> Dynamic IP		<b>DNS</b> Primary DNS <input type="text"/> Secondary DNS <input type="text"/>	
<b>Static IP</b> IP Address <input type="text" value="192.168.2.254"/> Netmask <input type="text" value="255.255.255.0"/> Gateway <input type="text" value="192.168.2.1"/>		<b>802.1d Spanning Tree</b> 802.1d Spanning Tree <input type="radio"/> Enable <input checked="" type="radio"/> Disable	
		<b>DHCP Forward</b> DHCP Forward <input type="radio"/> Enable <input checked="" type="radio"/> Disable	

- **Mode:** Administrator can select the IP used Static or Dynamic IP address.
  - Static IP : A set of fixed IP addresses can be manually set for the system to use.
  - Dynamic IP : If there is a DHCP server on the top, you can use the dynamic IP address to let the system obtain a set of IP automatically.

**Notice**

*That when using a dynamic IP, the system will automatically obtain the IP address sent by DHCP, and the obtained IP address will be obtained after the operation is confirmed by the upper DHCP server. Obtaining the IP address is not fixed. For system management, the upper DHCP server must query the IP address obtained by the current system.*

➤ **Static IP:**

<b>Static IP</b>	
IP Address	<input type="text" value="192.168.2.254"/>
Netmask	<input type="text" value="255.255.255.0"/>
Gateway	<input type="text" value="192.168.2.1"/>


- **IP address:** The IP address is 192.168.2.254
- **Netmask:** The default Netmask is 255.255.255.0
- **Gateway:** The default Gateway IP Address is 192.168.2.1, Please check your Gateway IP and change.
- **DNS:** Enter IP address of domain name service.

<b>DNS</b>	
Primary DNS	<input type="text" value="8.8.8.8"/>
Secondary DNS	<input type="text"/>




- **Primary DNS:** The IP address of the primary DNS server.
- **Secondary:** The IP address of the secondary DNS server.


➤ **802.1d Spanning Tree :**



The spanning tree network protocol provides a loop free topology for a bridged LAN between LAN interface and 8 WDS interfaces from wds0 to wds7. The Spanning Tree Protocol, which is also referred to as STP, is defined in the IEEE Standard 802.1d.




- **DHCP Forward:** When the AP Mode device and Client Bridge AP are linked, and DHCP Service is “Enabled”, the Client Bridge AP must also enable DHCP Forward to allow connecting clients to receive the IP Address from the source AP (AP Mode Device). By default, DHCP Forward is disabled in Client Bridge devices. This function must be enabled to allow clients connecting to the Client Bridge device to receive IP Addresses from the source AP.



Click “Save” button to save your set function. Then click “Reboot” button to activate your changes.

## 6.3 Configure DHCP Setup

The DHCP Service function in the Client Bridge device can select a separate IP Address range within the same network segment of the source AP, and allocate those IP Addresses to connecting clients.



- **Start IP / End IP:** Specify the range of IP addresses to be used by the DHCP server when assigning IP address to clients.
- **Netmask:** The netmask default is 255.255.255.0.
- **Gateway:** Enter source gateway IP address.
- **DNS1:** Enter IP address of the first DNS server; this field is required.
- **DNS2:** Enter IP address of the second DNS server; this is optional.
- **WINS IP:** Enter IP address of the Windows Internet Name Service (WINS) server; this is optional.
- **Domain:** Enter the domain name for this network.
- **Lease Time:** The IP addresses given out by the DHCP server will only be valid for the duration specified by the lease time. Increasing the time ensure client operation without interruptions, but

could introduce potential conflicts. Lowering the lease time will avoid potential address conflicts, but might cause more interruptions to the client while it will acquire new IP addresses from the DHCP server. Default is **86400** seconds

**DHCP Clients List:** When users link to CenOS 5.0 AP and use IP address of the DHCP service, the DHCP Client List will display users the information and used IP address.

DHCP Client List				
#	IP Address	MAC Address	Expired	Action
-	-	-	-	-

- **IP Address:** Display users used IP address.
- **MAC Address:** Display MAC Address of users used device.
- **Expired:** Display Lease expiration time of IP address.
- **Action:** Kicked user button.

**Static Lease IP Setup:** Administrator can set as static IP address for users.

Static Lease IP Setup	
<b>Comment</b>	<input type="text"/>
<b>IP Address</b>	<input type="text"/>
<b>MAC Address</b>	<input type="text"/> <input type="button" value="Add"/>

- **Comment:** Enter description for the information.
- **IP Address:** Set static IP address for users.
- **MAC Address:** Set MAC address of user device.


**Static Lease IP List:** Display users list of static IP address.

Static Lease IP List				
#	Comment	IP Address	MAC Address	Action
-	-	-	-	-

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 6.4 Wireless General Setup


The main setup Client Bridge connection to AP Station and Repeater AP functions setting, MAC filter, WMM and 802.11r/802.11k Fast Roaming etc in wireless menu.



**Notice** *When the upper limit of the 2.4G frequency is used, the repeater AP will only be able to use the other two 5G extension Repeater AP APs. If the upper end AP with a Radio 1 (5G) frequency is used, the repeater AP will only Use 2.4G as the extension Repeater AP base.*

### 6.4.1 Radio 0(2.4G) Basic Setup

Administrator can change the data transmission, channel and output power settings for the system.



**General Setup**

**MAC Address**

**Station Mode**  Enable  Disable

**Country**

**Band Mode**

**Tx Power**

**Slot Time**  Distance

**ACK Timeout**

- **Station Mode:** If Client Bridge want to use 2.4G link to Access Point then administrator can enable the function (radio 0).
- **Country:** Administrator can select country used channel by US and EU.
- **Band Mode:** Select an appropriate wireless band; bands available are **801.11 b/g/n mixed mode**.

- **Tx Power:** Administrator can adjust the output power of the system to get the appropriate coverage for your wireless network. Specify digit numbers between level **1** to level 9 (the unit is %) for your environment. If you are not sure which setting to choose, then keep the default setting level 9 (**100%**).
- **Slot Timeout :** You can enter the slot time value here. When the distance is long or short, the waiting time for packet transmission will be adjusted fast and slow.
- **Distance:** When the "Distance" button is clicked, the point-to-point bridge distance can be entered. The system will automatically calculate the ideal reference value for the Slot Time and ACK Timeout. The input distance is calculated in units (meters).
- **ACK Timeout :** When waiting for the "ACKnowledgment frame" interval is too long to be received, the ACK will be retransmitted. A higher ACK Timeout will reduce packet loss, but the transmission efficiency will be poor.

Setting Slot Time and ACK Timeout can strengthen the long-distance connection. Changing the value can optimize the setting. If the value is too low, the length transmission will be reduced. If the value is too high, there may be disconnection.

## HT Physical Mode

**HT Physical Mode**

<b>TX/RX Stream</b>	<input type="text" value="2T2R"/>
<b>Channel BandWidth</b>	<input type="text" value="20/40"/>
<b>MCS</b>	<input type="text" value="Auto"/>
<b>Short GI</b>	<input checked="" type="radio"/> <b>Enable</b> <input type="radio"/> <b>Disable</b>
<b>Aggregation</b>	<input checked="" type="radio"/> <b>Enable</b> <input type="radio"/> <b>Disable</b>
<b>Aggregation Frames</b>	<input type="text" value="32"/>
<b>Aggregation Size</b>	<input type="text" value="50000"/>


- **TX/RX Stream:** Build in 2.4GHz 2 antennas and support 2TX/2RX streams. Administrator can select 1 or 2 TX/RX. The default is 2TX/2RX.

This product has a built-in 2x2 (2T2R) antenna for 2.4Ghz, which has been matched with the default setting of 2T2R. If there is no special demand, please keep this default setting .

- **Channel Bandwidth:** The "20/40" MHz option is usually best. The other option is available for special circumstances.
- **MCS:** This parameter represents transmission rate. By default (Auto) the fastest possible transmission rate will be selected. You have the option of selecting the speed if necessary.
- **Shout GI:** Short Guard Interval, by default, it's "Enable". it's can increase throughput. However, it can also increase error rate in some installations, due to increased sensitivity to radio-frequency reflections. Select the option that works best for your installation.
- **Aggregation:** By default, it's "Enable". To "Disable" to deactivated Aggregation.  
A part of the 802.11n standard(or draft-standard). It allows sending multiple frames per single access to the medium by combining frames together into one larger frame.  
It creates the larger frame by combining smaller frames with the same physical source and destination end points and traffic class (i.e. QoS) into one large frame with a common MAC header.
- **Aggregation Frames:** Set frames size of Aggregation, the size recommend use default value is 32.
- **Aggregation Size:** Set aggregation size, the size recommends use default value is 500000.


Click "Save" button to save your set function. Then click "Reboot" button to activate your changes.

## 6.4.2 Radio 1 (5G) Basic Setup



General Setup	
MAC Address	8c:4d:ea:05:1c:76
Station Mode	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Country	Taiwan
Band Mode	802.11ac
Auto Channel	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Channel	100 (5500 Mhz)
Tx Power	Level 9
Slot Time	9 <span style="float: right; background-color: green; color: white; padding: 2px;">Distance</span>
ACK Timeout	30

- **MAC Address:** Display Radio 1(5G) used MAC address.
- **Country:** Administrator can select country used channel by US / EU and Taiwan.
- **Band Mode:** If Client Bridge want to use 5G link to Access Point then administrator can enable the function (Radio 1(5G).
- **Auto Channel:** Administrator can Enable or Disable the function. If select disable function the WiFi channel can be fixed a channel.
- **Channel:** Support US / EU / Taiwan country by 5G Channel.
- **Tx Power:** Administrator can control the WiFi Tx output power. The power Max. Level 9.
- **Slot Timeout :** You can enter the slot time value here. When the distance is long or short, the waiting time for packet transmission will be adjusted fast and slow.
- **Distance:** When the "Distance" button is clicked, the point-to-point bridge distance can be entered. The system will automatically calculate the ideal reference value for the Slot Time and ACK Timeout. The input distance is calculated in units (meters).
- **ACK Timeout :** When waiting for the "ACKnowledgment frame" interval is too long to be received,the ACK will be retransmitted. A higher ACK Timeout will reduce packet loss, but the transmission efficiency will be poor.



Setting Slot Time and ACK Timeout can strengthen the long-distance connection. Changing the value can optimize the setting. If the value is too low, the length transmission will be reduced. If the value is too high, there may be disconnection.

## HT Physical Mode

**HT Physical Mode**

**TX/RX Stream**

**Channel**

**BandWidth**

**Min MCS**

**Max MCS**

**Short GI**  Enable  Disable

**Aggregation**  Enable  Disable

**Aggregation Frames**

**Aggregation Size**

- **TX/RX Stream:** supporting 2TX/2RX streams. Administrator can select 1 or 2 TX/RX. The default is 2TX/2RX.


Notice

This product has a built-in 2x2 (2T2R) antenna for 5Ghz, which has been matched with the default setting of 2T2R. If there is no special demand, please keep this default setting .

- **Channel Bandwidth:** The "20/40 and 802.11ac 80" MHz option is usually best. The other option is available for special circumstances.
- **MIN MCS:** This parameter represents transmission rate. By default (4) the fastest possible transmission rate will be selected. You have the option of selecting the speed if necessary.
- **MAX MCS:** This parameter represents transmission rate. By default (9) the fastest possible transmission rate will be selected. You have the option of selecting the speed if necessary.
- **Shout GI:** Short Guard Interval, by default, it's "Enable". it's can increase throughput. However, it can also increase error rate in some installations, due to increased sensitivity to radio-frequency reflections. Select the option that works best for your installation.
- **Aggregation:** By default, it's "Enable". To "Disable" to deactivated Aggregation. A part of the 802.11n standard(or draft-standard). It allows sending multiple frames per single access to the medium by combining frames together into one larger frame. It creates the larger frame by combining smaller frames with the same physical source and destination end points and traffic class (i.e. QoS) into one large frame with a common MAC header.
- **Aggregation Frames:** Set frames size of Aggregation, the size recommend use default value is 32.
- **Aggregation Size:** Set aggregation size, the size recommends use default value is 500000.

Click "Save" button to save your set function. Then click "Reboot" button to activate your changes.

## 6.4.3 Advanced Setup



Advanced Setup	
Beacon Interval	<input type="text" value="100"/>
DTIM Interval	<input type="text" value="1"/>
Fragment Threshold	<input type="text" value="2346"/>
RTS Threshold	<input type="text" value="2346"/>
Short Preamble	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
IGMP Snooping	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Greenfield	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
RF on/off by Schedule	<input type="text" value="Always"/>
Location Tracking Log	<input type="checkbox"/> <input type="text" value="600"/> <input type="text" value="Seconds"/>



- **Beacon Interval:** Beacon Interval is in the range of **40~3500** and set in unit of *millisecond*. The default value is **100** msec.  
Access Point (AP) in IEEE 802.11 will send out a special approximated 50-byte frame, called “Beacon”. Beacon is broadcast to all the stations, provides the basic information of AP such as SSID, channel, encryption keys, signal strength, time stamp, support data rate.  
All the radio stations received beacon recognizes the existence of such AP, and may proceed next actions if the information from AP matches the requirement. Beacon is sent on a periodic basis, the time interval can be adjusted.  
By increasing the beacon interval, you can reduce the number of beacons and associated overhead, but that will likely delay the association and roaming process because stations scanning for available access points may miss the beacons. You can decrease the beacon interval, which increases the rate of beacons. This will make the association and roaming process very responsive; however, the network will incur additional overhead and throughput will go down.
- **DTIM Interval:** The DTIM interval is in the range of **1~255**. The default is **1**.  
DTIM is defined as *Delivery Traffic Indication Message*. It is used to notify the wireless stations, which support power saving mode, when to wake up to receive multicast frame. DTIM is necessary and critical in wireless environment as a mechanism to fulfill power-saving synchronization.  
A DTIM interval is a count of the number of beacon frames that must occur before the access point sends the buffered multicast frames. For instance, if DTIM Interval is set to 3, then the Wi-Fi clients will expect to receive a multicast frame after receiving three Beacon frame. The higher DTIM interval will help power saving and possibly decrease wireless throughput in multicast applications.
- **Fragmentation Threshold:** Fragmentation Threshold is one more parameter which is given in all stations and Access points. Fine tuning Fragmentation Threshold parameter can result in good throughput but not using it properly can result in low throughput. In simple words it does the same thing which MTU do in Ethernet. Both are different parameters but the work done is same, it fragments the data packets.  
Fragmentation threshold will be used when we have more data packet size to be transmitted and we have less fragment threshold value. Let’s say from Ethernet we have to send 1400 byte packet but the fragmentation threshold is set as 400. In this case when the packet is to be transmitted on air it will fragment the packet in to 4 small packet 400+400+400+200 and send on air. This includes MAC header+ frame body and CRC so 400 byte will be in total including headers. This helps in increasing the throughput. The default is 2346.
- **RTS Threshold:** RTS Threshold is in the range of **1~2347** byte. The default is **2347** byte.  
The main purpose of enabling RTS by changing RTS threshold is to reduce possible collisions

due to hidden wireless clients. RTS in AP will be enabled automatically if the packet size is larger than the Threshold value. By default, RTS is disabled in a normal environment supports non-jumbo frames.

- **Short Preamble:** By default, this function is “*Enabled*”. *Disabling* will automatically use the Long 128-bit Preamble Synchronization field. The preamble is used to signal "here is a train of data coming" to the receiver. The short preamble provides 72-bit Synchronization field to improve WLAN transmission efficiency with less overhead.
- **IGMP Snooping:** The process of listening to Internet Group Management Protocol (IGMP) network traffic. The feature allows a network switch to listen in on the IGMP conversation between hosts and routers. By listening to these conversations the switch maintains a map of which links need which IP multicast streams. Multicasts may be filtered from the links which do not need them and thus controls which ports receive specific multicast traffic.
- **Greenfield:** In wireless WLAN technology, greenfield mode is a feature of major components of the 802.11n specification. The greenfield mode feature is designed to improve efficiency by eliminating support for 802.11b/g devices in an all draft-n network. In greenfield mode the network can be set to ignore all earlier standards.
- **RF on/off by schedule:** Administrator can apply Time Policy to on or off wireless signal.
- **Location Tracking Log:** The system can detect the signal strength of the wireless client to determine the location of the Access Point and send to database.


```
Jan 1 08:28:00 Wifilogd: tm=1420072080 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=01-7-88-11-19 rssi=-67
Jan 1 08:27:00 Wifilogd: tm=1420072020 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=01-7-88-11-19 rssi=-68
Jan 1 08:26:00 Wifilogd: tm=1420071960 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=01-7-88-11-19 rssi=-67
```

Click “**Save**” button to save your set function. Then click “**Reboot**” button to activate your changes.

## 6.4.4 WMM Setup

This affects traffic flowing from the access point to the client station.

Configuring QoS options consists of setting parameters on existing queues for different types of wireless traffic. You can configure different minimum and maximum wait times for the transmission of packets in each queue based on the requirements of the media being sent. Queues automatically provide minimum transmission delay for Voice, Video, multimedia, and mission critical applications, and rely on best-effort parameters for traditional IP data.



As an Example, time-sensitive Voice & Video, and multimedia are given effectively higher priority for transmission (lower wait times for channel access), while other applications and traditional IP data which are less time-sensitive but often more data-intensive are expected to tolerate longer wait times.

WMM Parameters of Access Point					
AC Type	CWmin	CWmax	AIFS	TxOp Limit	No ACK Policy bit
AC_BE(0)	4	6	3	0	<input type="checkbox"/>
AC_BK(1)	4	10	7	0	<input type="checkbox"/>
AC_VI(2)	3	4	1	3008	<input type="checkbox"/>
AC_VO(3)	2	3	1	1504	<input type="checkbox"/>

WMM Parameters of Station					
AC Type	CWmin	CWmax	AIFS	TxOp Limit	ACM bit
AC_BE(0)	4	10	3	0	<input type="checkbox"/>
AC_BK(1)	4	10	7	0	<input type="checkbox"/>
AC_VI(2)	3	4	2	3008	<input type="checkbox"/>
AC_VO(3)	2	3	2	1504	<input type="checkbox"/>

➤ **AC Type :**

Queue	Data Transmitted AP to Clients	Priority	Description
AC_BK	Background	Low	High throughput. Bulk data that requires maximum throughput and is not time-sensitive is sent to this queue (FTP data, for example).
AC_BE	Best Effort	Medium	Medium throughput and delay. Most traditional IP data is sent to this queue.
AC_VI	Video	High	Minimum delay. Time-sensitive video data is automatically sent to this queue.
AC_VO	Voice	High	Time-sensitive data like VoIP and streaming media are automatically sent to this queue.

➤ **CWmin :**

Minimum Contention Window. This parameter is input to the algorithm that determines the initial random backoff wait time ("window") for retry of a transmission. The value specified here in the Minimum Contention Window is the upper limit (in milliseconds) of a range from which the initial random backoff wait time is determined. ◦

➤ **CWmax :** Maximum Contention Window. The value specified here in the Maximum Contention Window is the upper limit (in milliseconds) for the doubling of the random backoff value. This doubling continues until either the data frame is sent or the Maximum Contention Window size is reached. Once the Maximum Contention Window size is reached, retries will continue until a maximum number of retries allowed is reached. Valid values for the "cwmax" are 1, 3, 7, 15, 31, 63, 127, 255, 511, or 1024. The value for "cwmax" must be higher than the value for "cwmin". ◦


➤ **AIFS :** The Arbitration Inter-Frame Spacing Number specifies a wait time (in milliseconds) for data frames ◦

- **TxOP Limit** : Transmission Opportunity is an interval of time when a WME AP has the right to initiate transmissions onto the wireless medium (WM). This value specifies (in milliseconds) the Transmission Opportunity (TXOP) for AP; that is, the interval of time when the WMM AP has the right to initiate transmissions on the wireless network. ◦
- **ACM bit** : Admission Control Mandatory, ACM only takes effect on AC\_VI and AC\_VO. When you do not click Checkbox, it means that the ACM is controlled by the connecting AP. If you click Checkbox, it means that the Client is in charge ◦
- **No ACK policy bit** : Acknowledgment Policy, WMM defines two ACK policies: **Normal ACK** and **No ACK**. Click “**Checkbox**” indicates “**No ACK**”  
 When the no acknowledgement (No ACK) policy is used, the recipient does not acknowledge received packets during wireless packet exchange. This policy is suitable in the environment where communication quality is fine and interference is weak.  
 While the No ACK policy helps improve transmission efficiency, it can cause increased packet loss when communication quality deteriorates. This is because when this policy is used, a sender does not retransmit packets that have not been received by the recipient.  
 When the Normal ACK policy is used, the recipient acknowledges each received unicast packet. ◦

Click “**Save**” button to save your set function. Then click “**Reboot**” button to activate your changes.

## 6.4.5 Station Setup

The functions setting functions include Client Bridge link to AP station. Administrator can used “site survey” function to Search for AP stations.



- **MAC Address List:** The function can discovery AP Station and select want to link the AP station, please click site survey button.

**Notice**

*If want to discovery 2.4G station then administrator need to enable station mode in Radio 0 (2.4G) function page (reference manual 6.4.1 “Radio 0 Basic Setup”). Same practice if want to discovery 5G station will need to enable station mode in Radio 1(5G) function page (reference manual 6.4.2 “Radio 1(5G) Basic Setup”).*

Station Mode     Enable     Disable

- **Security:** After site survey AP station complete will list all AP station, when click AP station setup button then AP station information (ESSID/Security type) will display on page.
- **PassPhrase Settings:** Administrator need manual set correct ESSID security/Cipher type and pass phrase.


**Notice**

*If Security/Cipher selected or set PassPhrase is wrong, it will not be able to bridge normally.*

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 6.4.6 Repeater AP Setup


Administrators can configure ESSID, SSID broadcasting, Maximum number of client associations.



**Notice**

1. If want to use Repeater AP function then Client Bridge must determine connection to Access Point then Repeater AP can operate normally.
2. The default is enabling of Repeater AP. If want to used pure Client Bridge will can disable it.
3. When Client Bridge used 2.4G to connection station then Repeater AP function only used the other 5G Wi-Fi. Same practice If Client Bridge used Radio 1(5G) then Repeater AP only used Radio 0 (2.4G) Wi-Fi.

- **Access Point:** Administrator can Enable or Disable the Repeater AP function.
- **ESSID:** Enter the Repeater AP of ESSID name.
- **SSID Visibility:** The default it's Enable. When select Disable the SSID will not is discovered.
- **Client Isolation:** This function is Disabled by default. All clients will be isolated from each other, which mean they can't reach each other.
- **Connection Limit:** This function is Disabled by default. If select Enable, Administrator can limit Wi-Fi users the Quantity.
- **Authentication:** Select the desired security type from the drop-down list; the options are WPA-PSK, WPA2-PSK, WPA/WPA2-Enterprise and WEP 802.1X.



- **Open System:** Data are not unencrypted during transmission when this option is selected.
- **WPA/WPA2 Personal:** WPA/WPA2 is short for W-Fi Protected Access-Pre-Shared Key. WPA/WPA2 uses the same encryption way with WPA, and the only difference between them is that WPA/WPA2 recreates a simple shared key, instead of using the user's certification.

**PassPhrase Settings**

<b>WPA Mode</b>	Auto (WPA or WPA2) <span style="float: right;">▼</span>
<b>Cipher Type</b>	Auto <span style="float: right;">▼</span>
<b>Group Key Update Interval</b>	600 <span style="float: right; border: 1px solid #ccc; padding: 2px 5px;">Seconds</span>
<b>PassPhrase</b>	

- ✓ **WPA Mode:** Administrator can select security for Auto or only WPA or only WPA2.
- ✓ **Cipher Type:** Administrator can select use AES or TKIP with WPA / WPA2 encryption method.

**AES** is short for “**Advanced Encryption Standard**”, The AES cipher is specified as a number of repetitions of transformation rounds that convert the input plaintext into the final output of ciphertext. Each round consists of several processing steps, including one that depends on the encryption key. A set of reverse rounds are applied to transform ciphertext back into the original plaintext using the same encryption key.

**TKIP** is short for “**Temporal Key Integrity Protocol**”, TKIP scrambles the keys using a hashing algorithm and, by adding an integrity-checking feature, ensures that the keys haven't been tampered with.



- ✓ **Group Key Update Interval:** This time interval for re-keying GTK (broadcast/multicast encryption keys) in seconds. Enter the time-length required; the default time is 600 seconds.
- ✓ **Pass Phrase:** Enter the ESSID pass phrase.

Click “**Save**” button to save your set function. Then click “**Reboot**” button to activate your changes.




## 6.4.7 MAC Filter Setup

Administrator can setup allow or reject WiFi clients(MAC address) to access Repeater AP.



- **Rule:** Select the desired access control type from the drop-down list; the options are Disable, Allow or Reject.




- **Only Allow List MAC:** Define certain wireless clients in the list which will have granted access to the Access Point while the access will be denied for all the remaining clients – Action Type is set to “Only Allow List MAC”.

- **Only Deny List MAC:** Define certain wireless clients in the list which will have denied access to the Access Point while the access will be granted for all the remaining clients - Action Type is set to **“Only Deny List MAC”**.
- **MAC Address:** Enter MAC Address for WiFi Clients.
- **MAC Address List:** Display the MAC address of WiFi Clients.

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 6.4.8 802.11r Fast Roaming Setup

The system support 802.11r/802.11k function for 2.4G and 5G radio. 802.11r, which is the IEEE standard for fast roaming, introduces a new concept of roaming where the initial handshake with the new AP is done even before the client roams to the target AP.



**802.11r Fast Roaming**

**Fast Roaming Settings**

Mobility Domain	a1b2
R0 Key Lifetime	10000
Reassoc deadline	1000
R0/NAS Identifier	ap.example.com
R1 Identifier	000102030405
R1 Push	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

- **Mobility Domain:** MDID is used to indicate a group of APs (within an ESS, i.e., sharing the same SSID) between which a STA can use Fast BSS Transition.

Notice
Please enter 2-octet identifier as a hex string.

- **R0 Key Lifetime:** Default lifetime of the PMK-RO in minutes, the default is 10000, administrator can setting 1~65535.
- **Reassoc deadline:** Reassociation deadline in time units (TUs / 1.024 ms; range 1000~65535). The default is 1000.
- **R0/NAS Identifier:** PMK-RO Key Holder identifier. When using IEEE 802.11r, nas\_identifier must be set and must be between 1 and 48 octets long.
- **R1 Identifier:** PMK-R1 Key Holder identifier 6-octet identifier as a hex string.
- **R1 Push:** Administrator can select Enable or disable. If enable the function will automatically sent the R1 Key.

### R0 Key Address:

To enable roaming between multiple AP devices, AP1 must key in the MAC Address of AP2, and AP2 must key in the MAC Address of AP1. The NAS Identifier and 128-bit Key should be identical in both AP settings. This will enable device roaming between the two Access Points.

**R0 Key holders**

<b>MAC Address</b>	<input type="text" value="Destination MAC Address"/>
<b>NAS Identifier</b>	<input type="text" value="(1-48 octets)"/>
<b>128-bit Key</b>	<input type="text" value="128-bit key as hex string"/> <span style="float: right; background-color: green; color: white; padding: 2px 5px; border: none;">Add</span>

- **MAC Address:** Enter must key in the MAC Address of other AP
- **NAS Identifier:** Enter 1~48 octets of network domain name.
- **128-bit Key:** Enter Shared Key of 128 bit.

### R0 Key Holder List:

After setting "R0 Key holders" function the information will appear in list.

R0 Key Holder List				
#	MAC Address	NAS Identifier	128-bit Key	Action
-	-	-	-	-

### R1 Key Holder List:

Enter a unified set of R1 Key Holder identification certification.

**R1 Key Holders**

**MAC Address**

**R1 Identifier**

**128-bit Key**  Add

- **MAC Address:** Enter the main roaming device MAC address
- **R1 Identifier:** Enter Shared identifier.
- **128-bit Key:** Enter Shared Key of 128 bit.

### R1 Key Holder List:

After setting "R1 Key holders" function the information will appear in list.

R1 Key Holder List				
#	MAC Address	NAS Identifier	128-bit Key	Action
-	-	-	-	-

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 7. WISP Mode


WISP Mode is a router function, if the Telecom company permits wireless connection to their WAN, administrators can change the CenOS 5.0 AP to WISP Mode to connect to the wifi network. The WISP Mode support PPPoE / Static IP / Dynamic IP and PPTP for WAN, and support Repeater AP function.

**Notice**

Relevant to Dual Band Devices Only: If wireless WAN used 2.4G radio connection to Telecom company station, the Repeater AP radio only used 5G radio. So wireless WAN used 5G radio connection to Telecom company station, the Repeater AP radio only used 2.4G radio.

### 7.1 Change Setup mode

If the administrator needs to switch to WISP mode, Please click "System"-> " Mode Setup " to change WISP mode.





**Notice**


Please note that the LAN IP addresses in each mode are different from each other and will not continue. For the first time after switching modes, always perform access management on the LAN default IP address of 192.168.2.254

### 7.2 Configure WAN Setup


There are four connection types for the WAN port: **Static IP**, **Dynamic IP**, **PPPoE** and **PPTP**. Please click on **System -> WAN** and follow the below setting.



## WAN Setting



- **Static IP:** Users can manually setup the WAN IP address with a static IP provided by WISP.
  - **IP Address:** The IP address of the WAN port.
  - **IP Netmask:** The Subnet mask of the WAN port.
  - **IP Gateway:** The default gateway of the WAN port.
- **Dynamic IP:** Please consult with WISP for correct wireless settings to associate with WISP AP before a dynamic IP, along with related IP settings. If IP Address is not assigned, please double check with your wireless settings and ensure successful association. Also, you may go to **“WAN Information”** in the Overview page to click **Release** button to release IP address and click **Renew** button to renew IP address again.



**WAN Settings**


**Mode**

---

**Dynamic IP**

**Hostname**

- **Hostname** : The Hostname of the WAN port
- **PPPoE** : To create wireless PPPoE WAN connection to a PPPoE server in network.



**WAN Settings**

**Mode**

---

**PPPoE**

**User Name**

**Password**

**MTU**

**Reconnect Mode**

- **User Name** : Enter User Name for PPPoE connection
- **Password** : Enter Password for PPPoE connection
- **MTU**: By default, MTU is set to **1492** bytes. MTU stands for Maximum Transmission Unit. Consult with WISP for a correct MTU setting.
- **Reconnect Mode**: Administrator can select three function for Always On / On Demand / Manual.
  - ✓ **Always on** – A connection to Internet is always maintained.
  - ✓ **On Demand** – A connection to Internet is made as needed.
  - ✓ **Manual** – Click the “**Connect**” button on “**WAN Information**” in the Overview page to connect to the Internet.
- **PPTP**: The Point-to-Point Tunneling Protocol (PPTP) mode enables the implementation of secure multi-protocol Virtual Private Networks (VPNs) through public networks.

WAN Settings

**Mode** PPTP

---

PPTP

**User Name**

**Password**

**PPTP Server IP**

**WAN IP**

**Netmask**

**MTU**

**MPPE40**  Enable  Disable


**MPPE128**  Enable  Disable

**Reconnect Mode** Always On

- **User Name:** Enter account for PPTP.
  - **Password:** Enter user name account used password for PPTP.
  - **PPTP Server IP:** Enter remote IP address of PPTP Server.
  - **WAN IP:** The IP address of the WAN port.
  - **Netmask:** The Subnet mask of the WAN port.
  - **MTU:** By default, it's **1460** bytes. MTU stands for Maximum Transmission Unit. Consult with WISP for a correct MTU setting.
  - **MPPE40/128:** Microsoft Point-to-Point Encryption (MPPE) encrypts data in Point-to-Point Protocol (PPP)-based dial-up connections or Point-to-Point Tunneling Protocol (PPTP) virtual private network (VPN) connections. **128-bit** key (strong) and **40-bit** key (standard) MPPE encryption schemes are supported. MPPE provides data security for the PPTP connection that is between the VPN client and the VPN server.
  - **Reconnect Mode:** Administrator can select three function for Always On / On Demand / Manual.
    - ✓ **Always on** – A connection to Internet is always maintained.
    - ✓ **On Demand** – A connection to Internet is made as needed.
    - ✓ **Manual** – Click the **“Connect”** button on **“WAN Information”** in the Overview page to connect to the Internet.
- **MAC Clone**
- The MAC address is a 12-digit HEX code uniquely assigned to hardware as identification. Some ISPs require you to register a MAC address in order to access to Internet. If not, you could use




default MAC or clone MAC from a PC.



- **Default MAC Address:** Keep the default MAC address of WAN port on the system.
- **Manual MAN Address:** Enter the MAC address registered with your ISP.

### ➤ DNS


Check “No Default DNS Server” or “Specify DNS Server IP” radial button as desired to set up system DNS.



- **Primary DNS:** The IP address of the primary DNS server.
- **Secondary DNS:** The IP address of the secondary DNS server.

### ➤ NAT


The NAT support Enable and Disable Service



Click “**Save**” button to save your set function. Then click “**Reboot**” button to activate your changes.

## 7.3 Configure LAN Setup

Here are the instructions for how to setup the local IP Address and Netmask. Please click on **System** -> **LAN** and follow the below setting.



<b>Ethernet Connection Type</b> Mode <input checked="" type="radio"/> Static IP <input type="radio"/> Dynamic IP		<b>DNS</b> Primary DNS <input type="text"/> Secondary DNS <input type="text"/>	
<b>Static IP</b> IP Address <input type="text" value="192.168.2.254"/> Netmask <input type="text" value="255.255.255.0"/> Gateway <input type="text" value="192.168.2.1"/>		<b>802.1d Spanning Tree</b> 802.1d Spanning Tree <input type="radio"/> Enable <input checked="" type="radio"/> Disable	
		<b>DHCP Forward</b> DHCP Forward <input type="radio"/> Enable <input checked="" type="radio"/> Disable	

- **Mode:** Administrator can select the IP used Static or Dynamic IP address.
  - Static IP : A set of fixed IP addresses can be manually set for the system to use.
  - Dynamic IP : If there is a DHCP server on the top, you can use the dynamic IP address to let the system obtain a set of IP automatically.

That when using a dynamic IP, the system will automatically obtain the IP address sent by DHCP, and the obtained IP address will be obtained after the operation is confirmed by the upper DHCP server. Obtaining the IP address is not fixed. For system management, the upper DHCP server must query the IP address obtained by the current system.

➤ **Static IP:**


<b>Static IP</b>	
IP Address	<input type="text" value="192.168.2.254"/>
Netmask	<input type="text" value="255.255.255.0"/>
Gateway	<input type="text" value="192.168.2.1"/>

- **IP address:** The IP address is 192.168.2.254
  - **Netmask:** The default Netmask is 255.255.255.0
  - **Gateway:** The default Gateway IP Address is 192.168.2.1, Please check your Gateway IP and change.
- **DNS:** Enter IP address of domain name service.


<b>DNS</b>	
Primary DNS	<input type="text" value="8.8.8.8"/>
Secondary DNS	<input type="text"/>

- **Primary DNS:** The IP address of the primary DNS server.
- **Secondary:** The IP address of the secondary DNS server.


➤ **802.1d Spanning Tree :**



The spanning tree network protocol provides a loop free topology for a bridged LAN between LAN interface and 8 WDS interfaces from wds0 to wds7. The Spanning Tree Protocol, which is also referred to as STP, is defined in the IEEE Standard 802.1d.





- **DHCP Forward:** When the AP Mode device and Client Bridge AP are linked, and DHCP Service is “Enabled”, the Client Bridge AP must also enable DHCP Forward to allow connecting clients to receive the IP Address from the source AP (AP Mode Device). By default, DHCP Forward is disabled in Client Bridge devices. This function must be enabled to allow clients connecting to the Client Bridge device to receive IP Addresses from the source AP.



Click “Save” button to save your set function. Then click “Reboot” button to activate your changes.

## 7.4 Configure DHCP Setup

The DHCP Service function in the Client Bridge device can select a separate IP Address range within the same network segment of the source AP, and allocate those IP Addresses to connecting clients.

The image shows the 'DHCP Setup' configuration page with the following fields:

Start IP	192.168.2.100
End IP	192.168.2.140
Netmask	255.255.255.0
Gateway	192.168.2.1
DNS1 IP	192.168.2.1
DNS2 IP	
WINS IP	
Domain	
Lease Time	86400

- **Start IP / End IP:** Specify the range of IP addresses to be used by the DHCP server when assigning IP address to clients.
- **Netmask:** The netmask default is 255.255.255.0.
- **Gateway:** Enter source gateway IP address.
- **DNS1:** Enter IP address of the first DNS server; this field is required.
- **DNS2:** Enter IP address of the second DNS server; this is optional.
- **WINS IP:** Enter IP address of the Windows Internet Name Service (WINS) server; this is optional.
- **Domain:** Enter the domain name for this network.

- **Lease Time:** The IP addresses given out by the DHCP server will only be valid for the duration specified by the lease time. Increasing the time ensure client operation without interruptions, but could introduce potential conflicts. Lowering the lease time will avoid potential address conflicts, but might cause more interruptions to the client while it will acquire new IP addresses from the DHCP server. Default is **86400** seconds

**DHCP Clients List:** When users link to CenOS 5.0 AP and use IP address of the DHCP service, the DHCP Client List will display users the information and used IP address.

DHCP Client List				
#	IP Address	MAC Address	Expired	Action
-	-	-	-	-

- **IP Address:** Display users used IP address.
- **MAC Address:** Display MAC Address of users used device.
- **Expired:** Display Lease expiration time of IP address.
- **Action:** Kicked user button.

**Static Lease IP Setup:** Administrator can set as static IP address for users.

Static Lease IP Setup	
<b>Comment</b>	<input type="text"/>
<b>IP Address</b>	<input type="text"/>
<b>MAC Address</b>	<input type="text"/> <input type="button" value="Add"/>

- **Comment:** Enter description for the information.
- **IP Address:** Set static IP address for users.
- **MAC Address:** Set MAC address of user device.


**Static Lease IP List:** Display users list of static IP address.

Static Lease IP List				
#	Comment	IP Address	MAC Address	Action
-	-	-	-	-

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 7.5 Wireless General Setup


The main setup Client Bridge connection to AP Station and Repeater AP functions setting, MAC filter, WMM and 802.11r/802.11k Fast Roaming etc in wireless menu.



**Notice** *When the upper limit of the 2.4G frequency is used, the repeater AP will only be able to use the other two 5G extension Repeater AP APs. If the upper end AP with a Radio 1 (5G) frequency is used, the repeater AP will only Use 2.4G as the extension Repeater AP base.*

### 7.5.1 Radio 0 (2.4G) Basic Setup

Administrator can change the data transmission, channel and output power settings for the system.



**General Setup**

MAC Address: 8c:4d:ea:05:1c:75

Station Mode:  Enable  Disable

Country: Taiwan

Band Mode: 802.11b/g/n


Tx Power: Level 9

Slot Time: 9 Distance

ACK Timeout: 64

- **Station Mode:** If Client Bridge want to use 2.4G link to Access Point then administrator can enable the function (radio 0).
- **Country:** Administrator can select country used channel by US and EU.

- **Band Mode:** Select an appropriate wireless band; bands available are **801.11 b/g/n mixed mode**.
- **Tx Power:** Administrator can adjust the output power of the system to get the appropriate coverage for your wireless network. Specify digit numbers between level **1** to level 9 (the unit is %) for your environment. If you are not sure which setting to choose, then keep the default setting level 9 (**100%**).
- **Slot Timeout :** You can enter the slot time value here. When the distance is long or short, the waiting time for packet transmission will be adjusted fast and slow.
- **Distance:** When the "Distance" button is clicked, the point-to-point bridge distance can be entered. The system will automatically calculate the ideal reference value for the Slot Time and ACK Timeout. The input distance is calculated in units (meters).
- **ACK Timeout :** When waiting for the "ACKnowledgment frame" interval is too long to be received, the ACK will be retransmitted. A higher ACK Timeout will reduce packet loss, but the transmission efficiency will be poor.




**Notice** *Setting Slot Time and ACK Timeout can strengthen the long-distance connection. Changing the value can optimize the setting. If the value is too low, the length transmission will be reduced. If the value is too high, there may be disconnection.*

## HT Physical Mode

**HT Physical Mode**

<b>TX/RX Stream</b>	<input type="text" value="2T2R"/>
<b>Channel BandWidth</b>	<input type="text" value="20/40"/>
<b>MCS</b>	<input type="text" value="Auto"/>
<b>Short GI</b>	<input checked="" type="radio"/> <b>Enable</b> <input type="radio"/> <b>Disable</b>
<b>Aggregation</b>	<input checked="" type="radio"/> <b>Enable</b> <input type="radio"/> <b>Disable</b>
<b>Aggregation Frames</b>	<input type="text" value="32"/>
<b>Aggregation Size</b>	<input type="text" value="50000"/>

- **TX/RX Stream:** Build in 2.4GHz 2 antennas and support 2TX/2RX streams. Administrator can select 1 or 2 TX/RX. The default is 2TX/2RX.




**Notice** *This product has a built-in 2x2 (2T2R) antenna for 2.4Ghz, which has been matched with the default setting of 2T2R. If there is no special demand, please keep this default setting .*

- **Channel Bandwidth:** The "20/40" MHz option is usually best. The other option is available for special circumstances.
- **MCS:** This parameter represents transmission rate. By default (Auto) the fastest possible transmission rate will be selected. You have the option of selecting the speed if necessary.
- **Shout GI:** Short Guard Interval, by default, it's "Enable". it's can increase throughput. However, it can also increase error rate in some installations, due to increased sensitivity to radio-frequency reflections. Select the option that works best for your installation.
- **Aggregation:** By default, it's "Enable". To "Disable" to deactivated Aggregation. A part of the 802.11n standard(or draft-standard). It allows sending multiple frames per single access to the medium by combining frames together into one larger frame. It creates the larger frame by combining smaller frames with the same physical source and destination end points and traffic class (i.e. QoS) into one large frame with a common MAC header.
- **Aggregation Frames:** Set frames size of Aggregation, the size recommend use default value is 32.
- **Aggregation Size:** Set aggregation size, the size recommends use default value is 500000.

Click "Save" button to save your set function. Then click "Reboot" button to activate your changes.

## 7.5.2 Radio 1 (5G) Basic Setup




- **MAC Address:** Display Radio 1(5G) used MAC address.
- **Country:** Administrator can select country used channel by US / EU and Taiwan.
- **Band Mode:** If Client Bridge want to use 5G link to Access Point then administrator can enable



the function (Radio 1(5G)).

- **Auto Channel:** Administrator can Enable or Disable the function. If select disable function the WiFi channel can be fixed a channel.
- **Channel:** Support US / EU / Taiwan country by 5G Channel.
- **Tx Power:** Administrator can control the WiFi Tx output power. The power Max. Level 9.
- **Slot Timeout :** You can enter the slot time value here. When the distance is long or short, the waiting time for packet transmission will be adjusted fast and slow.
- **Distance:** When the "Distance" button is clicked, the point-to-point bridge distance can be entered. The system will automatically calculate the ideal reference value for the Slot Time and ACK Timeout. The input distance is calculated in units (meters).
- **ACK Timeout :** When waiting for the "ACKnowledgment frame" interval is too long to be received, the ACK will be retransmitted. A higher ACK Timeout will reduce packet loss, but the transmission efficiency will be poor.



Setting Slot Time and ACK Timeout can strengthen the long-distance connection. Changing the value can optimize the setting. If the value is too low, the length transmission will be reduced. If the value is too high, there may be disconnection.

## HT Physical Mode

**HT Physical Mode**

**TX/RX Stream**

**Channel**

**BandWidth**

**Min MCS**

**Max MCS**

**Short GI**  Enable  Disable

**Aggregation**  Enable  Disable

**Aggregation Frames**

**Aggregation Size**

- **TX/RX Stream:** supporting 2TX/2RX streams. Administrator can select 1 or 2 TX/RX. The default is 2TX/2RX.


**Notice**

*This product has a built-in 2x2 (2T2R) antenna for 5Ghz, which has been matched with the default setting of 2T2R. If there is no special demand, please keep this default setting .*

- **Channel Bandwidth:** The "20/40 and 802.11ac 80" MHz option is usually best. The other option is available for special circumstances.
- **MIN MCS:** This parameter represents transmission rate. By default (4) the fastest possible transmission rate will be selected. You have the option of selecting the speed if necessary.
- **MAX MCS:** This parameter represents transmission rate. By default (9) the fastest possible transmission rate will be selected. You have the option of selecting the speed if necessary.
- **Short GI:** Short Guard Interval, by default, it's "Enable". it's can increase throughput. However, it can also increase error rate in some installations, due to increased sensitivity to radio-frequency reflections. Select the option that works best for your installation.
- **Aggregation:** By default, it's "Enable". To "Disable" to deactivated Aggregation. A part of the 802.11n standard(or draft-standard). It allows sending multiple frames per single access to the medium by combining frames together into one larger frame. It creates the larger frame by combining smaller frames with the same physical source and destination end points and traffic class (i.e. QoS) into one large frame with a common MAC header.
- **Aggregation Frames:** Set frames size of Aggregation, the size recommend use default value is 32.
- **Aggregation Size:** Set aggregation size, the size recommends use default value is 500000.

Click "Save" button to save your set function. Then click "Reboot" button to activate your changes.

## 7.5.3 Advanced Setup



Advanced Setup	
Beacon Interval	<input type="text" value="100"/>
DTIM Interval	<input type="text" value="1"/>
Fragment Threshold	<input type="text" value="2346"/>
RTS Threshold	<input type="text" value="2346"/>
Short Preamble	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
IGMP Snooping	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Greenfield	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
RF on/off by Schedule	<input type="text" value="Always"/>
Location Tracking Log	<input type="checkbox"/> <input type="text" value="600"/> <input type="text" value="Seconds"/>

- **Beacon Interval:** Beacon Interval is in the range of **40~3500** and set in unit of *millisecond*. The default value is **100** msec.

Access Point (AP) in IEEE 802.11 will send out a special approximated 50-byte frame, called “Beacon”. Beacon is broadcast to all the stations, provides the basic information of AP such as SSID, channel, encryption keys, signal strength, time stamp, support data rate.

All the radio stations received beacon recognizes the existence of such AP, and may proceed next actions if the information from AP matches the requirement. Beacon is sent on a periodic basis, the time interval can be adjusted.

By increasing the beacon interval, you can reduce the number of beacons and associated overhead, but that will likely delay the association and roaming process because stations scanning for available access points may miss the beacons. You can decrease the beacon interval, which increases the rate of beacons. This will make the association and roaming process very responsive; however, the network will incur additional overhead and throughput will go down.

- **DTIM Interval:** The DTIM interval is in the range of **1~255**. The default is **1**.  
DTIM is defined as *Delivery Traffic Indication Message*. It is used to notify the wireless stations, which support power saving mode, when to wake up to receive multicast frame. DTIM is necessary and critical in wireless environment as a mechanism to fulfill power-saving synchronization.

A DTIM interval is a count of the number of beacon frames that must occur before the access point sends the buffered multicast frames. For instance, if DTIM Interval is set to 3, then the Wi-Fi clients will expect to receive a multicast frame after receiving three Beacon frame. The higher DTIM interval will help power saving and possibly decrease wireless throughput in

multicast applications.

- **Fragmentation Threshold:** Fragmentation Threshold is one more parameter which is given in all stations and Access points. Fine tuning Fragmentation Threshold parameter can result in good throughput but not using it properly can result in low throughput. In simple words it does the same thing which MTU do in Ethernet. Both are different parameters but the work done is same, it fragments the data packets.  
Fragmentation threshold will be used when we have more data packet size to be transmitted and we have less fragment threshold value. Let's say from Ethernet we have to send 1400 byte packet but the fragmentation threshold is set as 400. In this case when the packet is to be transmitted on air it will fragment the packet in to 4 small packet 400+400+400+200 and send on air. This includes MAC header+ frame body and CRC so 400 byte will be in total including headers. This helps in increasing the throughput. The default is 2346.
- **RTS Threshold:** RTS Threshold is in the range of **1~2347** byte. The default is **2347** byte. The main purpose of enabling RTS by changing RTS threshold is to reduce possible collisions due to hidden wireless clients. RTS in AP will be enabled automatically if the packet size is larger than the Threshold value. By default, RTS is disabled in a normal environment supports non-jumbo frames.
- **Short Preamble:** By default, this function is **"Enabled"**. **Disabling** will automatically use the Long 128-bit Preamble Synchronization field. The preamble is used to signal "here is a train of data coming" to the receiver. The short preamble provides 72-bit Synchronization field to improve WLAN transmission efficiency with less overhead.
- **IGMP Snooping:** The process of listening to Internet Group Management Protocol (IGMP) network traffic. The feature allows a network switch to listen in on the IGMP conversation between hosts and routers. By listening to these conversations the switch maintains a map of which links need which IP multicast streams. Multicasts may be filtered from the links which do not need them and thus controls which ports receive specific multicast traffic.
- **Greenfield:** In wireless WLAN technology, greenfield mode is a feature of major components of the 802.11n specification. The greenfield mode feature is designed to improve efficiency by eliminating support for 802.11b/g devices in an all draft-n network. In greenfield mode the network can be set to ignore all earlier standards.
- **RF on/off by schedule:** Administrator can apply Time Policy to on or off wireless signal.
- **Location Tracking Log:** The system can detect the signal strength of the wireless client to determine the location of the Access Point and send to database.


```
Jan 1 08:28:00 Wifilogd: tm=1420072080 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=[REDACTED] rssi=-67
Jan 1 08:27:00 Wifilogd: tm=1420072020 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=[REDACTED] rssi=-68
Jan 1 08:26:00 Wifilogd: tm=1420071960 vlan=0 radio=0 bssid=8c:4d:ea:05:1c:7a climac=[REDACTED] rssi=-67
```

Click **"Save"** button to save your set function. Then click **"Reboot"** button to activate your changes.

## 7.5.4 WMM Setup

This affects traffic flowing from the access point to the client station.

Configuring QoS options consists of setting parameters on existing queues for different types of wireless traffic. You can configure different minimum and maximum wait times for the transmission of packets in each queue based on the requirements of the media being sent. Queues automatically provide minimum transmission delay for Voice, Video, multimedia, and mission critical applications, and rely on best-effort parameters for traditional IP data.



As an Example, time-sensitive Voice & Video, and multimedia are given effectively higher priority for transmission (lower wait times for channel access), while other applications and traditional IP data which are less time-sensitive but often more data-intensive are expected to tolerate longer wait times.

WMM Parameters of Access Point					
AC Type	CWmin	CWmax	AIFS	TxOp Limit	No ACK Policy bit
AC_BE(0)	4	6	3	0	<input type="checkbox"/>
AC_BK(1)	4	10	7	0	<input type="checkbox"/>
AC_VI(2)	3	4	1	3008	<input type="checkbox"/>
AC_VO(3)	2	3	1	1504	<input type="checkbox"/>

WMM Parameters of Station					
AC Type	CWmin	CWmax	AIFS	TxOp Limit	ACM bit
AC_BE(0)	4	10	3	0	<input type="checkbox"/>
AC_BK(1)	4	10	7	0	<input type="checkbox"/>
AC_VI(2)	3	4	2	3008	<input type="checkbox"/>
AC_VO(3)	2	3	2	1504	<input type="checkbox"/>

➤ **AC Type :**

Queue	Data Transmitted AP to Clients	Priority	Description
AC_BK	Background	Low	High throughput. Bulk data that requires maximum throughput and is not time-sensitive is sent to this queue (FTP data, for example).
AC_BE	Best Effort	Medium	Medium throughput and delay. Most traditional IP data is sent to this queue.
AC_VI	Video	High	Minimum delay. Time-sensitive video data is automatically sent to this queue.
AC_VO	Voice	High	Time-sensitive data like VoIP and streaming media are automatically sent to this queue.

➤ **CWmin :**

Minimum Contention Window. This parameter is input to the algorithm that determines the initial random backoff wait time ("window") for retry of a transmission. The value specified here in the Minimum Contention Window is the upper limit (in milliseconds) of a range from which the initial random backoff wait time is determined. ◦

➤ **CWmax :** Maximum Contention Window. The value specified here in the Maximum Contention Window is the upper limit (in milliseconds) for the doubling of the random backoff value. This doubling continues until either the data frame is sent or the Maximum Contention Window size is reached. Once the Maximum Contention Window size is reached, retries will continue until a maximum number of retries allowed is reached. Valid values for the "cwmax" are 1, 3, 7, 15, 31, 63, 127, 255, 511, or 1024. The value for "cwmax" must be higher than the value for "cwmin". ◦

➤ **AIFS :** The Arbitration Inter-Frame Spacing Number specifies a wait time (in milliseconds) for data frames ◦

➤ **TxOP Limit :** Transmission Opportunity is an interval of time when a WME AP has the right to

initiate transmissions onto the wireless medium (WM). This value specifies (in milliseconds) the Transmission Opportunity (TXOP) for AP; that is, the interval of time when the WMM AP has the right to initiate transmissions on the wireless network. ◦

- **ACM bit** : Admission Control Mandatory, ACM only takes effect on AC\_VI and AC\_VO. When you do not click Checkbox, it means that the ACM is controlled by the connecting AP. If you click Checkbox, it means that the Client is in charge ◦
- **No ACK policy bit** : Acknowledgment Policy, WMM defines two ACK policies: **Normal ACK** and **No ACK**. Click “**Checkbox**” indicates “**No ACK**”

When the no acknowledgement (No ACK) policy is used, the recipient does not acknowledge received packets during wireless packet exchange. This policy is suitable in the environment where communication quality is fine and interference is weak.


While the No ACK policy helps improve transmission efficiency, it can cause increased packet loss when communication quality deteriorates. This is because when this policy is used, a sender does not retransmit packets that have not been received by the recipient.

When the Normal ACK policy is used, the recipient acknowledges each received unicast packet. ◦

Click “**Save**” button to save your set function. Then click “**Reboot**” button to activate your changes.

## 7.5.5 Station Setup

The functions setting functions include Client Bridge link to AP station. Administrator can used “site survey” function to Search for AP stations.



Channel	Signal	BSSID	ESSID	Authentication	Setup
-	-	-	-	-	-

- **MAC Address List:** The function can discovery AP Station and select want to link the AP station, please click site survey button.

**Notice** *If want to discovery 2.4G station then administrator need to enable station mode in Radio 0 (2.4G) function page (reference manual 7.5.1 “Radio 0 Basic Setup”). Same practice if want to discovery 5G station will need to enable station mode in Radio 1(5G) function page (reference manual 7.5.2 “Radio 1(5G) Basic Setup”).*

Station Mode    Enable    Disable

- **Security:** After site survey AP station complete will list all AP station, when click AP station setup button then AP station information (ESSID/Security type) will display on page.
- **PassPhrase Settings:** Administrator need manual set correct ESSID security/Cipher type and pass phrase.


**Notice** *If Security/Cipher selected or set PassPhrase is wrong, it will not be able to bridge normally.*

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.



## 7.5.6 Repeater AP Setup


Administrators can configure ESSID, SSID broadcasting, Maximum number of client associations.



**Notice**

1. If want to use Repeater AP function then Client Bridge must determine connection to Access Point then Repeater AP can operate normally.
2. The default is enabling of Repeater AP. If want to used pure Client Bridge will can disable it.
3. When Client Bridge used 2.4G to connection station then Repeater AP function only used the other 5G Wi-Fi. Same practice If Client Bridge used Radio 1(5G) then Repeater AP only used Radio 0 (2.4G) Wi-Fi.

- **Access Point:** Administrator can Enable or Disable the Repeater AP function.
- **ESSID:** Enter the Repeater AP of ESSID name.
- **SSID Visibility:** The default it's Enable. When select Disable the SSID will not is discovered.
- **Client Isolation:** This function is Disabled by default. All clients will be isolated from each other, which mean they can't reach each other.
- **Connection Limit:** This function is Disabled by default. If select Enable, Administrator can limit Wi-Fi users the Quantity.
- **Authentication:** Select the desired security type from the drop-down list; the options are WPA-PSK, WPA2-PSK, WPA/WPA2-Enterprise and WEP 802.1X.



- **Open System:** Data are not unencrypted during transmission when this option is selected.
- **WPA/WPA2 Personal:** WPA/WPA2 is short for W-Fi Protected Access-Pre-Shared Key. WPA/WPA2 uses the same encryption way with WPA, and the only difference between them is that WPA/WPA2 recreates a simple shared key, instead of using the user's certification.

**PassPhrase Settings**

<b>WPA Mode</b>	Auto (WPA or WPA2) <span style="float: right;">▼</span>
<b>Cipher Type</b>	Auto <span style="float: right;">▼</span>
<b>Group Key Update Interval</b>	600 <span style="float: right; border: 1px solid #ccc; padding: 2px 5px;">Seconds</span>
<b>PassPhrase</b>	

- ✓ **WPA Mode:** Administrator can select security for Auto or only WPA or only WPA2.
- ✓ **Cipher Type:** Administrator can select use AES or TKIP with WPA / WPA2 encryption method.

**AES** is short for “**Advanced Encryption Standard**”, The AES cipher is specified as a number of repetitions of transformation rounds that convert the input plaintext into the final output of ciphertext. Each round consists of several processing steps, including one that depends on the encryption key. A set of reverse rounds are applied to transform ciphertext back into the original plaintext using the same encryption key.



**TKIP** is short for “**Temporal Key Integrity Protocol**”, TKIP scrambles the keys using a hashing algorithm and, by adding an integrity-checking feature, ensures that the keys haven't been tampered with.

- ✓ **Group Key Update Interval:** This time interval for re-keying GTK (broadcast/multicast encryption keys) in seconds. Enter the time-length required; the default time is 600 seconds.
- ✓ **Pass Phrase:** Enter the ESSID pass phrase.


Click “**Save**” button to save your set function. Then click “**Reboot**” button to activate your changes.

## 7.5.7 MAC Filter Setup

Administrator can setup allow or reject WiFi clients(MAC address) to access Repeater AP.



- **Rule:** Select the desired access control type from the drop-down list; the options are Disable, Allow or Reject.



- **Only Allow List MAC:** Define certain wireless clients in the list which will have granted access to the Access Point while the access will be denied for all the remaining clients –

Action Type is set to **“Only Allow List MAC”**.


- **Only Deny List MAC:** Define certain wireless clients in the list which will have denied access to the Access Point while the access will be granted for all the remaining clients - Action Type is set to **“Only Deny List MAC”**.

- **MAC Address:** Enter MAC Address for WiFi Clients.
- **MAC Address List:** Display the MAC address of WiFi Clients.

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 7.5.8 802.11r Fast Roaming Setup

The system support 802.11r/802.11k function for 2.4G and 5G radio. 802.11r, which is the IEEE standard for fast roaming, introduces a new concept of roaming where the initial handshake with the new AP is done even before the client roams to the target AP.



The screenshot shows the 'Wireless' menu with '802.11r Fast Roaming' selected. Below it, the 'Fast Roaming Settings' page is displayed with the following configuration:

Fast Roaming Settings	
Mobility Domain	a1b2
R0 Key Lifetime	10000
Reassoc deadline	1000
R0/NAS Identifier	ap.example.com
R1 Identifier	000102030405
R1 Push	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

- **Mobility Domain:** MDID is used to indicate a group of APs (within an ESS, i.e., sharing the same SSID) between which a STA can use Fast BSS Transition.


Notice
*Please enter 2-octet identifier as a hex string.*

- **R0 Key Lifetime:** Default lifetime of the PMK-R0 in minutes, the default is 10000, administrator can setting 1~65535.
- **Reassoc deadline:** Reassociation deadline in time units (TUs / 1.024 ms; range 1000~65535). The default is 1000.
- **R0/NAS Identifier:** PMK-R0 Key Holder identifier. When using IEEE 802.11r, nas\_identifier must be set and must be between 1 and 48 octets long.
- **R1 Identifier:** PMK-R1 Key Holder identifier 6-octet identifier as a hex string.
- **R1 Push:** Administrator can select Enable or disable. If enable the function will automatically sent the R1 Key.

### R0 Key Address:

To enable roaming between multiple AP devices, AP1 must key in the MAC Address of AP2, and AP2 must key in the MAC Address of AP1. The NAS Identifier and 128-bit Key should be identical in both AP settings. This will enable device roaming between the two Access Points.

**R0 Key holders**

<b>MAC Address</b>	<input type="text" value="Destination MAC Address"/>
<b>NAS Identifier</b>	<input type="text" value="(1-48 octets)"/>
<b>128-bit Key</b>	<input type="text" value="128-bit key as hex string"/> <span style="float: right; background-color: #006600; color: white; padding: 2px 5px; border: 1px solid #006600;">Add</span>

- **MAC Address:** Enter must key in the MAC Address of other AP
- **NAS Identifier:** Enter 1~48 octets of network domain name.
- **128-bit Key:** Enter Shared Key of 128 bit.

### R0 Key Holder List:

After setting "R0 Key holders" function the information will appear in list.

R0 Key Holder List				
#	MAC Address	NAS Identifier	128-bit Key	Action
-	-	-	-	-

### R1 Key Holder List:

Enter a unified set of R1 Key Holder identification certification.

**R1 Key Holders**

**MAC Address**

**R1 Identifier**

**128-bit Key**  Add

- **MAC Address:** Enter the main roaming device MAC address
- **R1 Identifier:** Enter Shared identifier.
- **128-bit Key:** Enter Shared Key of 128 bit.

**R1 Key Holder List:**


After setting "R1 Key holders" function the information will appear in list.

R1 Key Holder List				
#	MAC Address	NAS Identifier	128-bit Key	Action
-	-	-	-	-


Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 7.6 Advanced Setup


Administrator can set basic routing security functions, including DMZ / IP and MAC filtering / virtual servers and access control management (basic firewall rules) in Advance menu.



### 7.6.1 DMZ



DMZ is commonly work with the NAT functionality as an alternative of Virtual Server(Port Forwarding) while wanting all ports of DMZ host visible to Internet users. Virtual Server rules have precedence over the DMZ rule. In order to use a range of ports available to access to different internal hosts Virtual Server rules are needed.



- **Automatic Assignment:** Enter Internal IP address of DMZ host and only one DMZ host is supported.



- **Internal IP Address:** Enter Virtual IP for service device.
- **Static Assignment:** Enter external and internal IP address of DMZ host. The function only external IP to Internal IP address

**Static Assignment Setup**


**External IP Address**

**Internal IP Address**  Add

- **External IP Address:** Enter external IP address
- **Internal IP Address:** Enter Virtual IP for service device.

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 7.6.2 IP Filter



Can allow or deny filter ingress or egress packets from specific source and/or to destination IP address on wired (LAN) or Wireless (WAN) ports. Filter rules could be used to filter unicast or multicast packets on different protocols as shown in the IP Filter Setup. Important to note that IP filter rules has precedence over Virtual server rules. Total of **20** rules maximum allowed in the IP Filter List. All rules can be edited or removed from the List.

#	Active	Comment	Protocol	In/Out	Action	Source Address/Mask	Source Port	Destination Address/Mask	Destination Port	Edit
1	InActive	-	ALL	In	Deny	-	-	-	-	Edit
2	InActive	-	ALL	In	Deny	-	-	-	-	Edit
3	InActive	-	ALL	In	Deny	-	-	-	-	Edit
4	InActive	-	ALL	In	Deny	-	-	-	-	Edit

Please click **Edit** button to setting IP filter.



- **Active:** Administrator can select Enable or Disable the service.
- **Comment:** Enter the description of IP filter rule.
- **Policy:** Administrator can select the IP flow rule of Deny or Pass.
- **In/ Out:** Administrator can select the IP flow rule of In/out bound.
- **Protocol:** Set used service Port of **TCP**, **UDP** or **ICMP**.
- **Source Address/Mask:** Enter desired source IP address and netmask. i.e. 192.168.2.10/32 or 192.168.2.10/255.255.255.0
- **Source Port:** Enter a port or a range of ports as **start:end**. i.e. port 20:80
- **Destination Address/Mask:** Enter desired destination IP address and netmask. i.e. 192.168.1.10/32 or 192.168.2.10/255.255.255.0
- **Destination Port:** Enter a port or a range of ports as **start:end**. i.e. port 20:80
- **Listen:** Select Enable radial button to match TCP packets only with the SYN flag.
- **Interface:** The interface that a filter rule applies.
- **Schedule:** Can choose to use rule by “Time Policy”.




**Notice**

*All packets are allowed by default. Deny rules could be added to the filter list to filter out unwanted packets and leave remaining allowed.*

Click “Save” button to save your set function. Then click “Reboot” button to activate your changes.

## 7.6.3 MAC Filter



Allows creating MAC filter rules to allow or deny unicast or multicast packets from limited number of MAC addresses. Important and must note. That MAC filter rules have precedence over IP Filter rules.

MAC Filter Rules

**Mode**

Disable
 

Disable  
Deny  
Allow


MAC Filter List

#	Active	Comment	MAC Address	Policy
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	Always Run <span style="font-size: x-small;">▼</span>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	Always Run <span style="font-size: x-small;">▼</span>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	Always Run <span style="font-size: x-small;">▼</span>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	Always Run <span style="font-size: x-small;">▼</span>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	Always Run <span style="font-size: x-small;">▼</span>

- **Mode:** Administrator can select Deny or Allow.
  - **Deny:** The MAC Filter List will be **denied** to access (LAN to WAN). Others will be allowed.
  - **Allow:** The MAC Filter List will be **allowed** to access (LAN to WAN). Others will be denied.
- **Comment:** Enter the description of MAC filter rule.
- **MAC Address:** Enter MAC address (e.g. aa:bb:cc:00:00:0a) and click **“Add”** button, then the MAC address should display in the MAC Filter List.
- **Policy:** Administrator can select to use rule by **“Time Policy”**.

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 7.6.4 Virtual Server



The “**Virtual Server**” can also referred to as “Port Forward” as well and used interchangeably. Resources in the network can be exposed to the Internet users in a controlled manner including on-line gaming, video conferencing or others via Virtual Server setup. Don’t repeat ports’ usage to avoid confusion.

Suppose you want to assign ports 21-25 to one FTP, Telnet and SMTP server (A in the example), and port 80 to another (B in the example). You assign the LAN IP addresses and the ISP assigns the WAN IP address. The NAT network appears as a single host on the Internet.

Virtual Server List							
#	Active	Comment	Protocol	Public Port	Private IP Address	Private Port	Edit
1	InActive	-	TCP	-	-	-	Edit
2	InActive	-	TCP	-	-	-	Edit
3	InActive	-	TCP	-	-	-	Edit
4	InActive	-	TCP	-	-	-	Edit
5	InActive	-	TCP	-	-	-	Edit
6	InActive	-	TCP	-	-	-	Edit
7	InActive	-	TCP	-	-	-	Edit

Please click **Edit** button to setting Virtual Server rules.

**Virtual Server Rules**

**Active**   
  **Enable**                     
  **Disable**

**Comment**   

**Protocol**   
  **TCP**                     
  **UDP**

**Public Port**   

**Private IP Address**   

**Private Port**   

**Schedule**

- **Active:** Administrator can select Virtual server rule to Enable or disable.
- **Comment:** Enter the description of virtual server rule.
- **Protocol:** Administrator can select service protocol of TCP or UDP.
- **Public Port:** Enter service port No. for public.
- **Private IP Address:** Enter corresponding IP address for internal.
- **Private Port:** Enter internal service port No. for private.
- **Schedule :** Administrator can select to used rule of **“Time Policy”**

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.

## 7.6.5 Access Control

The Access Control function administrator can to block or allow specific kinds of TCP/UDP/ICMP protocol, such as Internet access, designated services, and websites. The Access Control function can set 20 profiles.

Please click on **Advance -> Access Control** and follow the below setting.

Access Control List				
#	Active	Comment	Protocol	Edit
1	InActive	-	ANY	<a href="#">Edit</a>
2	InActive	-	ANY	<a href="#">Edit</a>
3	InActive	-	ANY	<a href="#">Edit</a>
4	InActive	-	ANY	<a href="#">Edit</a>
5	InActive	-	ANY	<a href="#">Edit</a>

- **# :** Display access control list.
- **Active :** Display Active or InActive for the access control rule.

- **Comment:** Display information for the rule.
- **Protocol :** Display information for the protocol.
- **Edit :** Administrator can click the button to set Access Control rule.

The screenshot shows two main configuration panels. The left panel, titled 'Access Control Rules', includes:
 

- Active:** Radio buttons for 'Enable' (selected) and 'Disable'.
- Comment:** A text input field containing 'TEST'.
- Protocol:** A dropdown menu currently set to 'ANY'.
- Schedule:** A dropdown menu currently set to 'Always'.

 Below this is the 'MAC Address Setup' section with a 'MAC Address' input field and an 'Add' button. At the bottom is the 'MAC Address List' table:
 

#	MAC Address	Action	#	MAC Address	Action
-	-	-	-	-	-

 The right panel, titled 'IP Address Setup', includes:
 

- Local IP Address:** Input fields for '192.168.2.100' and '192.168.2.200'.
- Local Port:** Input field for '80'.
- Destination IP Address:** Input fields for '0.0.0.0' and an empty field.
- Destination Port:** Input field for '80'.

### # Access control rules :

- **Active :** Administrator can select Enable or Disable for the Access control rule.
- **Comment :** Administrator can enter comment for the role.
- **Protocol :** Administrator can to select management protocol by TCP/UDP/ICMP/Content Filter/Application and Domain Filter.

The screenshot shows the 'Protocol' dropdown menu expanded. The options listed are:
 


- ANY
- TCP
- UDP
- ICMP
- Content Filter
- Application
- Domain Filter

- ✓ **ANY:** Select "Any" is all deny Protocol, administrator can filter local IP / IP range go to destination IP / IP range and use protocol.
- ✓ **TCP:** Deny TCP Protocol, Administrator can set TCP protocol and assign IP / IP range.
- ✓ **UDP:** Deny UDP Protocol, Administrator can set UDP protocol and assign IP / IP range.
- ✓ **ICMP:** Deny ICMP Protocol, Administrator can assign IP / IP range.
- ✓ **Content Filter:** Administrator can set web Keyword to filter.
- ✓ **Application:** System built-in multiple applications data, Administrator can select application data to filter.
- ✓ **Domain:** Administrator can set domain name to filter.
- **Schedule :** The rule can apply Time Policy.

Click **“Save”** button to save your set function. Then click **“Reboot”** button to activate your changes.


## 8. Utilities

Administrator can backup or restore system configuration / firmware Upgrade / ping tools and system reset to default or reboot system.




### 8.1 Profile Setting


This Functions purpose is to backup current configuration, restore prior configuration or reset back to factory default configurations.



please click on **Utilities** -> **Profile Setting** and follow the below setting




- **Save Settings to PC:** Click **Save** button to save the current configuration to a local disk.



- **Load Settings from PC:** Click **Browse** button to locate a configuration file to restore, and then click **Upload** button to upload.
- **Reset To Factory Default:** Click **Default** button to reset back to the factory default settings and expect **Successful** loading message. Then, click **Reboot** button to activate.

## 8.2 System Upgrade



Firmware is the main software image that system needs to respond to requests and to manage real time operations. Firmware upgrades are sometimes required to include new features or bugs fix. It takes around 2 minutes to upgrade due to complexity of firmware. To upgrade system firmware, click Browse button to locate the new firmware, and then click Upgrade button to upgrade.

### **Firmware Information:**

Display the system firmware information.

Firmware Information

Sometimes it may be necessary to reboot the system if it begins working improperly. Rebooting the system will not delete any of your configuration settings. Click reboot button to reboot the system.

**Firmware Version**

**Firmware Date**

---

Upgrade Via Local PC

**Select File**

---

Upgrade Via TFTP Server


**TFTP Server IP**

**File Name**

➤ **Select File:** Administrator can select Firmware file in Local PC.

### Upgrade Via Local PC and TFTP Server:

The upgrade firmware will support via local PC and TFTP Server and HTTP URL to upgrade system.



Notice

*We strongly recommend that you perform the firmware update by following these steps:*


- 1. Please use a RJ-45 network cable to connect the computer and the wireless base AP mode to perform the update operation. Do not use a wireless connection for firmware update operations.*
- 2. During the update process, please do not turn off or power off the system.*
- 3. Make sure to update using a compatible web browser to avoid update failures.*
- 4. After the update is complete, make sure to perform a factory default reset operation and restart the wireless AP mode.*
- 5. If the update operation is not performed according to the above steps, if the update fails and the system cannot provide services or cannot operate normally, please forgive us for treating this situation as a human error and you will lose the product warranty. Service and you will be charged for related maintenance.*



## 8.3 Network Utility



The administrator can diagnose network connectivity via the PING or TRACEROUTE utility. Please click on **Utilities** -> **Network Utility** and follow the below setting.




- **Ping:** This utility will help ping other devices on the network to verify connectivity. Ping utility, using ICMP packets, detects connectivity and latency between two network nodes. As result of that, packet loss and latency time are available in the **Result** field while running the PING test.
  - **IP/Domain :** Enter desired domain name, i.e. www.google.com, or IP address of the destination, and click ping button to proceed. The ping result will be shown in the Result field.
  - **Count :** By default, its 5 and the range is from 1 to 50. It indicates number of connectivity test.
- **Traceroute :** Allows tracing the hops from the CenOS 5.0 AP device to a selected outgoing IP address. It should be used for the finding the route taken by ICMP packets across the network to the destination host. The test is started using the **Start** button, click **Stop** button to stopped test.
  - **Destination Host:** Specifies the Destination Host for the finding the route taken by ICMP packets across the network.
  - **MAX Hop:** Specifies the maximum number of hops (max time-to-live value) trace route will probe.


## 8.4 Reboot




This function allows user to restart system with existing or most current settings when changes are made. Click **Reboot** button to proceed and take around three minutes to complete.



## 9. Status




The status mainly displays system related information, including system network information, wireless base station information, and wireless user connection information.



## 9.1 Overview

Detailed information on System, Network can be reviewed via this page.



### Overview :

It mainly displays the current mode, name, time, firmware version, network card address and related network settings.


### Information :

Shows the performance / memory usage of the total CPU space used by the current system and the current number of connected wireless users. °




### Radio 0 / Radio 1 wireless Information :

Displays the basic operating mode information of the current Radio 0 (2.4GHz) / Radio 1 (5GHz) wireless AP.



Radio	Band Mode	Channel	Rate
Radio 0	802.11b/g/n	5	400.0 Mb/s
Radio 1	802.11ac	132	0.0 Mb/s

## 9.2 Wireless Client





The page can be display Wireless user information link to access point. Administrator can monitor MAC address / rate and RSSI for the wireless users. (In addition to CAP mode)

VLAN 0			
Radio	MAC Address	Rate(RX/TX)	RSSI
-	-	-	-

- **Radio** : Display information for wireless client connection Radio 0 or 1
- **MAC Address** : Display information of clients Wi-Fi MAC address
- **Rata(Tx/Rx)** : Display information of clients Wi-Fi connection data rete.
- **RSSI** : Display information of clients Wi-Fi connection signal strong and weak.

## 9.3 Online Users





**Notice**

*This function works in the wireless AP mode. When the web authentication function is activated, the current connection status and related information of online users who have passed the authentication will be displayed. (Please refer to Manual 4.2 "Authentication" Function)*

The status can display online users by Captive Portal. Administrator can monitor user's login / logout time and account type for the authentication account. (This page only used AP mode)

Authentication Zone Online Users

VLAN#	Authentication	User Count	Download Packets	Upload Packets	Download Bytes	Upload Bytes	Action
0	ON	1	76842	17677	98.41MB	2.09MB	Detail
1	OFF	0	0	0	0B	0B	-


- **VLAN#** : Display VLAN number.
- **Authentication** : Display Captive Portal authentication function is on/off in the VLANs.
- **Users Count** : Display the VLAN network connected user’s amount.
- **Download Packets** : Display total download packets amount information of the VLAN.
- **Upload Packets** : Display total upload packets amount information of the VLAN.
- **Download Bytes** : Display total download flow information of the VLAN.
- **Upload Bytes** : Display total upload flow information of the VLAN.
- **Action** : Administrator can click “Detail” button to monitor all user’s use network information.

Authentication Zone 0 Online Users

#	Auth Type	Username	IP Address	MAC Address	Login Time	Download Packets	Upload Packets	Download Bytes	Upload Bytes	Action
1	Local	test	192.168.2.21	XXXXXXXXXX:2A	2016/01/01 00:23:41	76842	17677	98.41MB	2.09MB	Logout

- **Auth Type** : Display authentication login type.
- **User name** : Display authentication account.
- **IP Address** : Display IP address for user.
- **MAC Address** : Display MAC address for user.
- **Download Packets** : Display total download packets amount information by user.
- **Upload Packets** : Display total upload packets amount information by user.
- **Download Bytes** : Display total download flow information by user.
- **Upload Bytes** : Display total upload flow information by user.

## 9.4 Authentication Log



**Notice**


*This function works in the wireless AP mode. When the web authentication function is activated, the current connection status and related information of online users who have passed the authentication will be displayed. (Please refer to Manual 4.2 “Authentication” Function)*

The authentication log can monitor account login/logout type and account use time. (This page only used AP mode)

Authentication Zone Log		
Date	VLAN#	Detail
-	-	-

- **Date:** Administrator can select dates.
- **VLAN:** Administrator can select VLANs.
- **Detail:** Administrator can click button to open detail information.

## 9.5 System Log



The system log displays system events when system is up and running. Also, it becomes very useful as a troubleshooting tool when issues are experienced in system.

System Log				Refresh	Clear
Time	Facility	Severity	Message		
2015-01-01 08:17:21	Wireless	Info	ath01: STA e4:46:da:65:c9:08 IEEE 802.11: associated		
2015-01-01 08:17:21	Wireless	Info	ath01: STA e4:46:da:65:c9:08 RADIUS: starting accounting session 6BBFAC8D-0000000A		
2015-01-01 08:17:57	Wireless	Info	ath01: STA e4:46:da:65:c9:08 IEEE 802.11: disassociated		
2015-01-01 08:17:58	Wireless	Info	ath01: STA e4:46:da:65:c9:08 IEEE 802.11: associated		
2015-01-01 08:17:58	Wireless	Info	ath01: STA e4:46:da:65:c9:08 RADIUS: starting accounting session 6BBFAC8D-0000000B		

- **Time :** The date and time when the event occurred.
- **Facility :** It helps users to identify source of events such “System” or “User”
- **Severity :** Severity level that a specific event is associated such as “info”, “error”, “warning”, etc.
- **Message :** Description of the event.
- Click “Refresh” button to renew the log
- Click “Clear” button to clear all the record.

## 10. [ Other technical documents]

### 10.1 Point to Point / Multi-Point for WDS settings


The WDS function is applied in the wireless AP mode. This function is mainly used for point-to-point wireless AP bridging. For the setting method, you can refer to the manual 4.5.5 "WDS Setting". This document mainly guides the key WDS procedures. Can easily structure WDS point-to-point or point to multi point applications

- 1) If point-to-point bridging is used for WDS function, it is recommended to use our products to avoid compatibility issues.
- 2) If point-to-point bridging is used for WDS function, it is recommended to use our products to avoid compatibility issues.
- 3) According to the requirements to be applied to 2.4G or 5G, please make sure that each wireless AP sets a set of same channels (**please refer to the manual 4.5 "Wireless Configuration" (Radio 0 or Radio 1 Setup)**)
- 4) Restart after confirmation will complete WDS point-to-point bridging, **please refer to the manual 4.5.6 "WDS Status"** to confirm the RSSI value. The value if show to "-1" indicates that the connection is not successful, please re-confirm whether the configuration file follows the above instructions, or between APs. Signals are blocked by interference.
- 5) Please refer to WDS setting page, please set the MAC address information of other wireless for the wireless AP correctly. If two bridges, Radio A and Radio B, are used as examples, the MAC address information of Radio B must be entered in the MAC address list of Radio A of the site, and, the MAC address information of Radio A must be entered in the MAC address list of Radio B of the site.

**Ps, The RSSI value is recommended to fall between 40 ~ 60. If over the RSSI value means the AP is too close to the AP. If below the RSSI value means the signal is not right or the distance is too far.**

**Remark:**

Because the WDS application is in the wireless AP mode, if the WDS function is enabled, it will be an AP + WDS application. If the wireless AP is not required to use the WDS function purely, **you can refer to the manual 4.1 "VLAN Setup" instructions**, turn off the wireless AP, as shown below.







## 10.2 Apply CERIO web authentication login page sample

If the device uses our company's wireless AP CenOS5.0, and the web authentication function is enabled, you will be able to customize the web authentication page. You can follow the steps below to easily complete the sample login page.


Step 1 : Start the web page authentication function first, and in the “System” settings => “Authentication” function (refer to Manual 4.2 "Authentication" function)




Authentication Setup			
VLANList			
#	VLAN Mode	Authentication	Action
0	On	off	Authentication



**Step 2 :** After confirming the activation, you can choose what type of login account to use. This step uses “Local User” as an example, and will “enable to create a Local User”. After confirming the activation, and “Save it”, See as follows.




**Step 3 :** Please go to the pull-down function button of the authentication function, and enter the “User Name” and “password” , See as follows.




The screenshot shows a web interface for user authentication. On the left, a dark sidebar contains a menu with 'Authentication' highlighted in green. A dropdown menu is open under 'Authentication', listing options: Guest, Local User (highlighted with a red box), OAuth 2.0, POP3/IMAP Server, Customize Page, Language, Walled Garden, Privilege Address, and Profile. To the right, the 'Local User' configuration form is visible, featuring a 'User Name' field with 'Local User' entered, a 'Password' field with '(4-32 chars)' as a placeholder, and a green 'Add' button.

- \* If want to use the system preset page, please refer to **step 4**,
- \* If want to apply our template, please refer to below for **step 5**,
- \* If want to edit the webpage by yourself, please refer to **step 7**.




**Notice** *If you want to edit the webpage by yourself, it is recommended that the administrator must have the basic ability to make webpages in HTML / CSS.) This department has no responsibility for webpage syntax guidance.*

**Step 4 :** If you want to use the preset authentication page, you can refer to the instruction **manual 4.2 “Customized Page”**, you will be able to set the preset Format for color editing and revision, if you need to customize the page and apply our template, **please refer to step 5**




**Step 5 :** The image file of the login page must be placed on the website server, the website address must be whitelisted. The background image of this example is stored on below second server (URL: [www.serio.com.tw](http://www.serio.com.tw)), so please make sure Enter into Walled Garden.




**Step 6 :** Go to the company's Cerio website to download the sample file first. And open your download sample, select all the HTML syntax and copy it, then paste it on the custom edit page of the system and save it.


Download example address: [www.cerio.com.tw/eng/extreme-indoor/customized-page/](http://www.cerio.com.tw/eng/extreme-indoor/customized-page/)




Close "Template" first, then copy the sample html\_code syntax and replace it in the HTML source code edit "Customize HTML Source code" bar.



After clearing the HTML source code content, then paste all the downloaded source code into the field, save and restart the device, and you can finish editing the login page.



**Login page for template below :**





Notice


1. This part must be within 190 lines. If the written HTML / CSS and other source code exceeds a certain line, it is recommended to save the CSS source code to the remote Web server, and then enter the IP address of the remote web server. Within Walled Garden. (Please refer to the manual 4.2 "Walled Garden" setting instructions)
2. This device does not support the storage space of picture files. If necessary, store the picture files on a remote web server and call the address recently, See as above.

**Step 7 :** If the custom page is to be make by yourself, the original code of the following scarlet letters must not be removed, others will be able to make by themselves

```
<html>
<head>
  <title>Hotspot</title>
  <script src="/javascripts/login.js" charset="utf-8" type="text/javascript"></script>
</head>
<body>
  <div class="container"></div>
</body>
</html>
```

**Step 8 :** The login function of this system is displayed by default. If there are unnecessary fields, specific fields can be hidden by CSS syntax, as explained below

Add the **<style> class** tag in the syntax and then add **{display: none;} </ style>** as the following example, find the ID code of the field to be hidden by the browser, for example, to hide the "Please Sign in" description, then find out its Class ID as shown below.



Add `<style>.form-signin-heading {display: none;} </style>` in the head to hide the description “Please Sign in” as shown in the figure below, and find the Please Sign in word disappeared, and so on.

User Name  Password

Remember me

## Appendix A. WEB GUI Valid Characters

**Table B WEB GUI Valid Characters**

Block	Field	Valid Characters
LAN	IP Address	IP Format; 1-254
	IP Netmask	128.0.0.0 ~ 255.255.255.252
	IP Gateway	IP Format; 1-254
	Primary DNS	IP Format; 1-254
	Secondary DNS	IP Format; 1-254
	Hostname	Length : 32 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] / ; ` , . =
DHCP Server	Start IP	IP Format; 1-254
	End IP	IP Format; 1-254
	DNS1 IP	IP Format; 1-254
	DNS2 IP	IP Format; 1-254
	WINS IP	IP Format; 1-254
	Domain	Length : 32 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] / ; ` , . =
	Lease Time	600 ~ 99999999

**Table B WEB GUI Valid Characters (continued)**

Block	Field	Valid Characters
Management	System Name/ Location	Length : 32 0-9, A-Z, a-z Space ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] / ; ` , . =
	Description	32 chars
	Password	Length : 4 ~ 30 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] / ; ` , . =
	HTTP/ HTTPS Port	1 ~ 65535
	Telnet/ SSH Port	1 ~ 65535



Block	Field	Valid Characters
<b>SNMP</b>	RO/RW community	Length : 32 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] ; ` , . =
	RO/RW user	Length : 31 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] ; ` , . =
	RO/RW password	Length : 8 ~ 32 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] ; ` , . =
	Community	Length : 32 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] ; ` , . =
	IP	IP Format; 1-254
<b>General Setup</b>	Tx Power	1-100 %
<b>Wireless Profile</b>	Profile Name	32 chars
	ESSID	Length : 31 Space 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] / ; ` , . =
	WEP Key	10, 26 HEX chars or 5, 13 ASCII chars
<b>Advanced Setup</b>	Pre-shared Key	8 ~ 63 ASCII chars; 64 HEX chars
	Beacon Interval	20 ~ 1024
	Date Beacon Rate	1 ~ 255
	Fragment Threshold	256 ~ 2346
	RTS Threshold	1 ~ 2347

**Table B WEB GUI Valid Characters (continued)**

Block	Field	Valid Characters
<b>Virtual AP Setup</b>	ESSID	Length : 31 Space 0-9, A-Z, a-z ~ ! @ # \$ % ^ * ( ) _ + - { }   : < > ? [ ] / ; ` , . =
	Maximum Clients	1 ~ 32
	VLAN ID	1 ~ 4094
	WEP Key	10, 26 HEX chars or 5, 13 ASCII chars
	Group Key Update Period	>=60 seconds
	PMK Cache Period	> 0 minute
	Pre-Shared Key	8 ~ 63 ASCII chars; 64 HEX chars

Block	Field	Valid Characters
WDS Setup	Radius Server IP	IP Format; 1-254
	Radius Port	1 ~ 65535
	Shared Secret	8 ~ 64 characters
	Session Timeout	>= 60 seconds; 0 is disable
	AES Key	8 ~ 63 ASCII chars; 64 HEX chars
	Peer's MAC Address	12 HEX chars
IP Filter	Description	32 chars
	Source Address	IP Format; 1-254
	Source Mask	0 ~ 32
	Source Port	1 ~ 65535
	Destination Address	IP Format; 1-254
	Destination Mask	0 ~ 32
	Destination Port	1 ~ 65535
MAC Filter	MAC address	MAC Format; 12 HEX chars
Virtual Server	Description	32 chars
	Private IP	IP Formate; 1-254
	Private/ Public Port	1 ~ 65535