

issales@cerio.com.tw Tel: +(886) 2-8911-6160 Fax: +(886) 2-8911-6180

News Release

TRI-BAND



RUGGED OUTDOOR AP. THREE RADIOS INSIDE FOR YOU.



BEST PERFORMANCE FOR LONG-DISTANCE
PTP AND PTMP APPLICATIONS (ow-500 A1 / OW-500 A3)



Perfect for deployment in enterprise, government, public outdoor environments application

- Supports a maximum throughput of 2.2Gbps, up to 400Mbps on the 2.4GHz frequency band and 867Mbps on the 5GHz (Radio1) frequency band and 867Mbps on the 5GHz (Radio2) frequency band
- Operation Modes: Access Point Mode (includes Hotspot Portal Authentication, Pure AP Mode, and AP + WDS Mode), Control Access Point Mode (Centralized AP Management), Client Bridge + Repeater Mode, and WISP / CPE Repeater Mode
- ♦ Supports 2.4/5/5GHz Tri-Band function and 4 external N-Type connectors are assigned to the 5GHz band and one built-in 2.4GHz 5dBi High-Gain Antenna (OW-500 A3)
- Supports 2.4/5/5GHz Tri-Band function and built in 18dBi 2x2 5GHz Directional Panel Antenna, 5dBi 2.4GHz High-Gain Antenna and support 2 external N-Type connectors are assigned to the 5GHz band (OW-500 A1)



issales@cerio.com.tw Tel: +(886) 2-8911-6160 Fax: +(886) 2-8911-6180

News Release

- ♦ Supports 2 10/100/1000Mbps Gigabit Ethernet Port and ETH1 port supports PoE function with IEEE 802.3af/at Power over Ethernet supported
- CenOS5.0 Control Access Point Mode supports centralized management of up to 64 APs
- ♦ With IP68 weather-proof durable design are made to withstand harsh environment deployment

TRI-BAND VS. DUAL-BAND APPLICATION COMPARISON





MOUNTING INSTALLATION










SURGE PROTECTOR (OPTIONAL)





Outdoor Type **POE-OSP**

Indoor Type **POE-ISP**





More detailed information:

• Outdoor AP







