



# IEEE 802.3at Multi Giga PoE Splitter

## Separate to DC/Power and Ethernet/Data

The CERIO POE-PD04S+ provides **Multi Gigabit Ethernet** and supports **IEEE 802.3at/af PoE** standards. It supports an excellent design of **hot-switching protection** to prevent failures caused by overload, which can prevent failures caused by instantaneous switching of different voltages. The equipment will not cause any damage when the voltage output is changed during operation. It provides **DC 12V or 19V or 24V** needs for any network or non-network equipment through DC to DC Cable which is included with package. It can take advantage of Power Over Ethernet and place Multi Giga/Giga/Fast Ethernet-enabled products, such as Wireless Access Points, Network Cameras, and VoIP Phone where power outlets are not readily available.

### 1/2.5/5Gbps Multi Gigabit IEEE 802.3at PoE Splitter



- ✧ Complying with IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3bz 2500 /5000 BASE-T, IEEE 802.3at/af PoE standards.
- ✧ Supports **Multi Gigabit (1/2.5/5Gbps)** Ethernet connection ability.
- ✧ Use to connect non-PoE 802.3at/af devices to PoE injector or PoE switch.
- ✧ Supports Output Volt hot switching for **12VDC/ 19VDC/24VDC three range adjustable**.
- ✧ Split the PoE signal into separate data and power, the **total distance up to 100M**.
- ✧ Supports power reverse acute protection design, and auto restarts to protect possible short circuit, which can reduce the damage caused by the short circuit.
- ✧ When using Active or Passive PoE 30Watts or up as input, the maximum power output up to 27Watts.
- ✧ Bundle accessories for inside diameter 2.1 mm (PHY) to 2.1 (PHY) mm DC cable.



## Product Application

It supports IEEE 802.3at PoE+/802.3af PoE standards and provides PoE 44~57V Ethernet power + data input to separate to only DC/Power output and only Ethernet/Data output.

**Cerio 802.3AT 30W Power Multi Gigabit Splitter applied to Non-PoE devices from 12V to 24VDC**

**POE-G30I**

12V~24V 11ac/11ax DC Input  
Multi-Giga WIFI Access Point

Max. Forward 27Watt DC Power through the Splitter

Multi Gigabit with Cat6 Cable

**POE-PD04S+**

30Watt 1/2.5/5Gbps Multi Gigabit Internal Power PoE Injector  
( This model is by optional )

12V~24V DC Input  
Multi-Giga IP CAM

DC Power 12V 19V 24V(Max.)

Max. Forward 27Watt DC Power trough the Splitter

802.3at 30Watt Power for 1/2.5/5Gbps Multi Gigabit Splitter

Multi Gigabit with Cat6 Cable

**POE-G30T**

30Watt 1/2.5/5Gbps Multi Gigabit External Power with STB PoE Injector  
( This model is by optional )

up to 100Meter distance

up to 100Meter distance

\* The 802.3AT power splitter allows a non compliant device to upgrade to PoE .It is used to deploy remote non-PoE devices with no nearby AC outlets.

## Hardware Overview

DC12V or 19V or 24V Power OUT DATA OUT

Wall Mount Holes

Unit Combination

STATUS LED

DC Output Control Switch 12V or 19V or 24V

POWER + DATA IN

Support 12VDC, 19VDC or 24VDC three range adjustable.

Output Voltage SW

12V 19V 24V



For more detailed product information, please visit our official [CERIO website](http://www.cerio.com.tw), [Facebook](https://www.facebook.com/cerio), or contact our international sales team at [issales@cerio.com.tw](mailto:issales@cerio.com.tw).

More detailed information :  
[• POE-PD04S+](#)

